Metallic Fixture Whips

Reduced Wall Galvanized Steel Flexible Metal Conduit - UL Listed



Conduit

Reduced Wall Galvanized
 Steel Flexible Metal Conduit

Conductors

· Solid or Stranded Copper

Conductor Insulation

- · THHN/THWN: 14 AWG & 12 AWG
- · TFN: 18 AWG & 16 AWG

Neutral Conductors

· White 120/208V

Grounding

 Insulated Green Copper Grounding Conductor¹

References & Rating


- · UL 66, 83 and 514B, File No. E96572
- NEC® 348
- Made in USA of US and /or imported materials


Maximum Temperature Rating

90°C (Dry)

Maximum Voltage Rating

· 600V





Conductor	Conduit	Product Code	
Trade Size	Trade Size x Length(ft)	30 Units Per Package	100 Units Per Package
	So	lid	
18-4 Solid (Black, White, Red, Green)	3/8 x 6	4523-21	4523-30
18-3 Solid (Black, White, Green)	3/8 x 6	4522-21	4522-30
18-2 Solid (Black, White)	3/8 x 6	4521-21	4521-30
16-4 Solid (Black, White, Red, Green)	3/8 x 6	4513-21	4513-30
16-3 Solid (Black, White, Green)	3/8 x 6	4512-21	4512-30
16-2 Solid (Black, White)	3/8 x 6	4511-21	4511-30
14-4 Solid (Black, White, Red, Green)	3/8 x 6	4503-21	4503-30
14-3 Solid (Black, White, Green)	3/8 x 6	4502-21	4502-30
14-2 Solid (Black, White)	3/8 x 6	4501-21	4501-30
12-4 Solid (Black, White, Red, Green)	3/8 x 6	4580-21	4580-30
12-3 Solid (Black, White, Green)	3/8 x 6	4579-21	4579-30
12-2 Solid (Black, White)	3/8 x 6	4578-21	4578-30
	Stra	nded	
18-4 Stranded (Black, White, Red, Green)	3/8 x 6	4623-21	4623-30
18-3 Stranded (Black, White, Green)	3/8 x 6	4622-21	4622-30
18-2 Stranded (Black, White)	3/8 x 6	4621-21	4621-30
16-4 Stranded (Black, White, Red, Green)	3/8 x 6	4613-21	4613-30
16-3 Stranded (Black, White, Green)	3/8 x 6	4612-21	4612-30
16-2 Stranded (Black, White)	3/8 x 6	4611-21	4611-30
14-4 Stranded (Black, White, Red, Green)	3/8 x 6	4603-21	4603-30
14-3 Stranded (Black, White, Green)	3/8 x 6	4602-21	4602-30
14-2 Stranded (Black, White)	3/8 x 6	4601-21	4601-30
12-4 Stranded (Black, White, Red, Green)	3/8 x 6	4680-21	4680-30
12-3 Stranded (Black, White, Green)	3/8 x 6	4679-21	4679-30
12-2 Stranded (Black, White)	3/8 x 6	4678-21	4678-30

Note: *Special Order, subject to lead times and minimum order quantities

%" whips have screw in die cast connectors on the 18AWG, 16AWG & 14AWG and set screw die cast for the 12AWG.

 $\label{lem:available} Available\ with\ customer\ specified\ connectors\ by\ special\ order.$

All whips are available in barrels and cartons.

<u>www.atkore.com</u> <u>ECFC-SPEC-6241-2403</u>

Metallic Fixture Whips



Reduced Wall Galvanized Steel Flexible Metal Conduit - UL Listed

Conductor	Conduit	Product Code	
Trade Size	Trade Size x Length(ft)	15 Units Per Package	50 Units Per Package
	s	olid	
14-4 Solid (Black, White, Red, Green)	1/2 x 6	4703-15	4703-24
14-3 Solid (Black, White, Green)	1/2 x 6	4702-15	4702-24
14-2 Solid (Black, White)	1/2 x 6	4701-15	4701-24
12-4 Solid (Black, White, Red, Green)	1/2 x 6	4706-15	4706-24
12-3 Solid (Black, White, Green)	1/2 x 6	4705-15	4705-24
12-2 Solid (Black, White)	1/2 x 6	4704-15	4704-24
	Stra	anded	
14-4 Stranded (Black, White, Red, Green)	1/2 x 6	4803-15	4803-24
14-3 Stranded (Black, White, Green)	1/2 x 6	4802-15	4802-24
14-2 Stranded (Black, White)	1/2 x 6	4801-15	4801-24
12-4 Stranded (Black, White, Red, Green)	1/2 x 6	4806-15	4806-24
12-3 Stranded (Black, White, Green)	1/2 x 6	4805-15	4805-24
12-2 Stranded (Black, White)	1/2 x 6	4804-15	4804-24

Note: *Special Order, subject to lead times and minimum order quantities

www.atkore.com ECFC-SPEC-6241-2403

^{1/2&}quot; whips have screw in die cast connectors.

Available with customer specified connectors by special order.

All whips are available in barrels and cartons.

'Two wire configuration do not have a insulated green copper grounding conductor.