



TAG \_\_\_\_\_

ARCHITECTURAL & ENGINEERING SPECIFICATION

Polished chrome-plated 8" [203mm] widespread faucet with a 5" [127mm] centerline cast brass low profile spout, slow-closing metering cartridges, and vandal-resistant ADA compliant color-coded metal handles. Easily adjustable cycle time, preset to 10 seconds. Unit is furnished with a water conserving aerator, an integral shank filter assembly, mounting hardware and 1/2" NPSM coupling nuts for standard lavatory risers.

\*Note: By nature, warm/hot water causes 1-2 seconds lower flow time than cold water.

Zurn Lead Free products (-XL) is the line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with Section 1417 of the Safe Drinking Water Act (SDWA) which mandates the weighted average lead content of no more than 0.25% of the wetted surface.

PRODUCT FEATURES

- Polymer Metering Cartridge Sleeve
- Chrome-plated cast brass widespread body
- Adjustable centers from 6" to 20"
- Color Coded Brass Metering Handle
- Adjustable Cycle Timing

COMPLIANCE AND CERTIFICATION:

- Lead Free Compliant
- ADA Compliant



AERATOR OPTIONS

	FLOWRATE GPM [LPM]	VANDAL RESISTANT	PRESSURE COMPRESSION	OUTLET TYPE
<b>-3M</b>	0.5 [1.9]	☑	☑	Spray
<b>-7M</b>	1.0 [3.8]		☑	Spray
<b>-16M</b>	1.0 [3.8]	☑	☑	Spray
<b>-22M</b>	1.0 [3.8]	☑		Laminar
<b>-25M</b>	0.35 [1.3]	☑	☑	Spray
<b>-28M</b>	0.5 [1.9]	☑		Laminar

\*Note: 0.35 GPM aerator typically maxes out around 10 second run time

SUFFIX OPTIONS

- G 1-1/4" [32mm] Grid Strainer Drain
- ICT Inter-connecting Copper Supply Tubes for 8" In-line Centers
- IN Institutional Handle - Tamper-Proof and Vandal-Resistant
- RKR ADA Compliant Rocker Handle

ARCHITECTURAL & ENGINEERING APPROVAL

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

Rough-in/Overview dimensions

