


Bloomington



Colors



White VTL BMWH




Sand VTL BMSA



Gray VTL BMGR



Dark Gray VTL BMDG




Black VTL BMBL


Sizes



24" x 47" x 9mm and 20mm Rectified



24" x 24" x 9mm and 20mm Rectified



12" x 24" x 9mm Rectified

BLOOMINGTON

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
24" x 47" Textured 20mm Rectified	23.63" x 47.25"	20.00mm	Bush-Hammered
24" x 47" Rectified	23.63" x 47.25"	9.00mm	Matte/Natural
24" x 24" Textured 20mm Rectified	23.63" x 23.63"	20.00mm	Bush-Hammered
24" x 24" Rectified	23.63" x 23.63"	9.00mm	Matte/Natural
24" x 24" Textured Rectified	23.63" x 23.63"	9.00mm	Bush-Hammered
12" x 24" Rectified	11.81" x 23.63"	9.00mm	Matte/Natural

* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.

Mosaics & Coordinating Trims*

SIZE	ACTUAL	FINISH
4" x 4" Mosaic Rectified	11.81" x 11.81"	Matte/Natural
12" x 12" Brick Mosaic Rectified	11.81" x 11.81"	Matte/Natural
3" x 24" Bullnose Rectified	2.81" x 23.63"	Matte/Natural
13" x 47" Scalino Rectified	13.00" x 47.25"	Matte/Natural
13" x 25" Scalino Rectified	13.00" x 23.63"	Matte/Natural
13" x 13" Step Tread Corner	13.00" x 13.00"	Matte/Natural

Recommended Grout Joint: 1/8" - Rectified
3/16" - Non Rectified

Product Characteristics

	BUSH-HAMMERED	MATTE/NATURAL
Breaking Strength (ASTM C648 or ISO 10545-4)	> 10000 N	≥ 1300N
Chemical Resistance (ASTM C650 or ISO 10545-13)	Resistant	Resistant
DCOF	> 0.42	> 0.42
Deep Scratch Resistance - Unglazed (ISO 10545-6)	≤ 145 mm3	≤ 145 mm3
Frost Resistance (ASTM C1026 or ISO 10545-12)	Resistant	Resistant
Mohs Hardness - EN101	N/A	N/A
Water Absorption (ASTM C373 or ISO 10545-3)	≤ 0.1%	≤ 0.1%
Certifications	LEED Certified	LEED Certified
Country of Origin	Italy	Italy
Shade Variation Code	V2	V2

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	•

** These recommendations are not defined by ANSI Standards

Material

Porcelain



Made in Italy



Import



V2 Slight Variation



DCOF: >0.42



LEED Certified



Scan QR Code for Product Information and Installation Images

Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com



VITL
COMMERCIAL SURFACES