

DARE TO BE BOLD



CHATEAU RESERVE™

COLORBODY™ PORCELAIN STONEWARE

TRUEDGE™ | REVEAL IMAGING® | STEPWISE™

MARAZZI 

DARE TO BE BOLD™



PHOTO FEATURES CHATEAU RESERVE™ IN SHADOW MOUNTAIN

CHATEAU RESERVE™

CHATEAU RESERVE™ is the latest introduction into Marazzi's expansive wood-look tile collection. Offered in a visually stunning 48" plank size, CHATEAU RESERVE™ features a lightly distressed European Oak finish with tight graining that enhances the authentic chatter cut graphics. Its revolutionary StepWise™ technology adds superior slip resistance, vastly expanding use to outdoors as well as commercial spaces, plus ease of cleaning. Five on-trend color ranges set this special blend apart adding richness to varying design styles.



Only our wood-look tile takes the beauty of wood into **unexpected spaces**



STEPWISE™
UP TO 75% MORE SLIP RESISTANCE THAN ORDINARY TILE*

SLIP-RESISTANT TECHNOLOGY

Provides a Dynamic Coefficient of Friction (DCOF) that is among the highest in the industry

BUILT-IN DURABILITY

StepWise™ technology is infused into the tile and will not wear off

INNOVATIVE DESIGN

Revolutionary technology allows for a wider array of applications in commercial and residential spaces

*When compared to tile meeting ANSI Standards

CHATEAU RESERVE™

COLORBODY™ PORCELAIN STONEWARE

TRUEEDGE™ | REVEAL IMAGING® | STEPWISE™



CR40 Hickory Grove



CR41 La Petit Greige



CR42 Shadow Mountain



CR43 Rustic Lodge



CR44 Woodland Chalet

USAGE

Floors	Walls	Countertops
F	W	C

CHATEAU RESERVE™

COLORBODY™ PORCELAIN STONEWARE

TRUEEDGE™ | REVEAL IMAGING® | STEPWISE™

SIZES

	Thickness	Sq. Ft./ Carton	Pieces/ Carton
12 x 48 Floor Tile (11-5/8" x 46-7/8") (30.48 cm x 121.92 cm)	3/8"	11.40	3
8 x 48 Floor Tile (7-3/4" x 46-7/8") (20.32 cm x 121.92 cm)	3/8"	15.18	6
6 x 48 Floor Tile (5-3/4" x 46-7/8") (15.24 cm x 121.92 cm)	3/8"	15.12	8

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	■
Wet & Level - Interior Floor	≥ 0.42	■
Shower Floors (Residential or Light Commercial)	≥ 0.42	■*
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	■
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit marazzitile.com/DCOF.

APPLICATION NOTES:

Floor tile is suitable for many residential and commercial floors.
Floor tile suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.
*Suitable only when a linear drain system is used and proper installation methods are followed

- Floor Tile
- Wall Tile
- TruEdge™
- Reveal Imaging®
- StepWise™
- Pre-Consumer Recycled Content



All or select items within this series meet the requirements for these qualifications. For more information visit marazzitile.com.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)	Moderate (V3)

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: marazzitile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazzitile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.



SLIP-RESISTANT TECHNOLOGY **BUILT-IN DURABILITY** **INNOVATIVE DESIGN**

Provides a Dynamic Coefficient of Friction (DCOF) that is among the highest in the industry

StepWise™ technology is infused into the tile and will not wear off

Revolutionary technology allows for a wider array of applications in commercial and residential spaces

*When compared to tile meeting ANSI Standards

MARAZZI 

DARE TO BE BOLD™

7834 C.F. Hawn Freeway
Dallas, Texas 75217

www.marazzitile.com
contact@marazzitile.com

©2017 Marazzi | 06.17 | MZBRO110 Chateau Reserve™ Brochure

COVER FEATURES CHATEAU RESERVE™ IN HICKORY GROVE

Color and other aesthetic features shown are as close as the limitation of the printing process will allow. We have tried to make this brochure as comprehensive and factual as possible. We reserve the right, however, to make changes at any time, without notice, in colors, materials, packaging, specifications and availability. Since some information may have been updated since time of printing, please check with Marazzi Customer Service for details.