



# Smart-UPS On-Line 120/208 V

Provides On-Line power protection for servers, voice/data networks, medical labs, and critical applications.



[apc.com](http://apc.com)

Life Is On

**Schneider**  
Electric



# A versatile UPS developed for unstable power conditions worldwide

Smart-UPS™ On-Line provides high-density, double-conversion online power protection for servers, voice/data networks, medical labs, and light industrial applications. The Smart-UPS On-Line is capable of supporting loads from 1 kVA to 10 kVA in a rack/tower convertible chassis. The 6 kVA, 8 kVA, and 10 kVA models feature unity output power factor enabling them to support power-hungry blade servers or heavily loaded equipment racks. When business-critical systems require runtime in hours, not minutes, Smart-UPS On-Line can be configured with multiple battery packs to meet aggressive runtime demands.

The included PowerChute™ Network Shutdown management software provides unattended graceful shutdown of network operating systems. Models 5 kVA to 10 kVA include an integrated network management card for remote management. The entire Smart-UPS On-Line family provides value to customers with demanding power conditions, including a very wide input voltage window, extremely tight output voltage regulation, frequency regulation, internal bypass, and input power factor correction.

# Smart-UPS On-Line

Industry-leading power factor maximizing UPS density  
Rackmount and Tower SRT 1 kVA – 10 kVA



SRT5KXLT shown

## Standard features

### Best-in-class power density

More real power in watts, 0.82 pf on the 2.2 kVA, 0.9 pf on the 1kVA, 1.5 kVA, and 3 kVA, 0.85 pf on 5 kVA, Unity on 6 kVA – 10 kVA units.

### High-efficiency “Green Mode”

Achieves 97% efficiency, which helps save utility and cooling costs without compromising performance or reliability. Energy Star® compliant.

### Graphical LCD display with multicolor backlight

Intuitive interface provides detailed and accurate information with ability to configure locally.

### Intelligent battery management

Temperature-compensated charging extends battery life and advanced algorithms recommend replacement date. The UPS can inform the user which batteries need to be replaced and auto detect when additional battery packs are added.

### Built-in energy meter

Measures energy use and displays UPS efficiency in various modes of operation for easy energy tracking.

### Operate without battery

Ability to immediately help protect equipment when power returns after a complete discharge of the battery.


### Three-year warranty on electronics

Additional year of warranty protection for electronics provides peace of mind.



# Smart-UPS On-Line

Proven performance with the world's largest installed base of single-phase, double-conversion products  
Rackmount and Tower SRT 1 kVA – 10 kVA



SRT10KXLT shown

## Additional features

**Embedded network management card with environmental monitoring (on the NC and 5 kVA – 10 kVA models)**

Remote monitoring and control of the UPS and the environment via Ethernet connection while freeing up the SmartSlot™ so customers can add accessories for additional communication options.

### Switched outlet group(s)

Ability to control a group of output load receptacles independent from the main UPS. Enables:

- Rebooting hung device without cycling the entire UPS
- Sequenced turn on/off
- Shedding of noncritical loads based on a variety of parameters (battery time, runtime remaining, and overload)
- Scheduled time off to conserve energy

### Emergency power off (EPO)

Remote UPS shutoff in the event of a fire or other emergency. The UPS can accept normally open (NO) or normally closed (NC) contacts.

### Communication ports

Serial, USB, Ethernet, and SmartSlot for network accessory cards.

### Communication protocols

Modbus Serial, USB PowerSummary, HTTP, SNMP, and Telnet.

Intuitive, easy-to-use LCD provides clear and accurate information in multiple languages



Backlight screens:

Amber: Indication of condition that requires attention

Red: Indication of UPS alarm that requires immediate attention

## Standard features

### LCD display screen

Accurately provides real-time status updates in your choice of basic or advanced menus.

### UPS status (scrolling)

- Output voltage
- Input voltage
- Output frequency
- Run time
- Load
- Battery health

### Control

- UPS and outlet group settings
- Bypass control

### Configuration

- Output voltage, frequency
- Language, brightness, contrast
- Alarm volume
- IP address

### Test and diagnostics

- Initiate battery and runtime calibration tests

### About

- UPS serial number, battery part number
- Battery install and suggested replacement dates

# Product accessories

## Management cards

- AP9640: UPS Network Management Card
- AP9641: UPS Network Management Card with Environmental Monitoring
- AP9643: UPS Network Management Card with Environmental Monitoring and Modbus Support
- AP9810: APC dry contact I/O accessory
- AP9624: UPS interface expander
- AP9613: dry contact I/O SmartSlot card

## Battery packs

- SRT192BP: APC Smart-UPS SRT 192 V 5 kVA and 6 kVA battery pack
- SRT192RMBP: APC Smart-UPS SRT 192 V 5 kVA and 6 kVA RM battery pack
- SRT192BP2: APC Smart-UPS SRT 192 V 8 kVA and 10 kVA battery pack
- SRT192RMBP2: APC Smart-UPS SRT 192 V 8 kVA and 10 kVA RM battery pack
- SRT48BP: APC Smart-UPS SRT 48 V 1 kVA and 1.5 kVA battery pack
- SRT48RMBP: APC Smart-UPS SRT 48 V 1 kVA and 1.5 kVA RM battery pack
- SRT72BP: APC Smart-UPS SRT 72 V 2.2 kVA battery pack
- SRT72RMBP: APC Smart-UPS SRT 72 V 2.2 kVA RM battery pack
- SRT96BP: APC Smart-UPS SRT 96 V 3 kVA battery pack
- SRT96RMBP: APC Smart-UPS SRT 96 V 3 kVA RM battery pack
- SRT002: APC Smart-UPS SRT 15 ft. extension cable for 192 VDC external battery packs 5/6 kVA UPS
- SRT003: APC Smart-UPS SRT 15 ft. extension cable for 192 VDC external battery packs 8/10 kVA UPS

- SRT009: APC Smart-UPS SRT 15 ft. extension cable for 72 VDC external battery pack 2.2 kVA UPS
- SRT010: APC Smart-UPS SRT 15 ft. extension cable for 96 VDC external battery pack 3 kVA UPS
- SRT013: APC Smart-UPS SRT 15 ft. extension cable for 48 VDC external battery pack

## Rail kits

- SRTRK2: APC Smart-UPS SRT 19 inch rail kit for Smart-UPS SRT 5/6/8/10 kVA
- SRTRK3: APC Smart-UPS SRT 2 post mounting rail kit for Smart-UPS SRT 2.2/3/5/8/10 kVA
- SRTRK4: APC Smart-UPS SRT 19 inch rail kit for Smart-UPS SRT 2.2/3 kVA

## Backplate kit

- SRT001: APC Smart-UPS SRT 5 kVA output HW kit
- SRT004: APC Smart-UPS SRT 5 kVA PDU, 208 V (4) L6-20
- SRT005: APC Smart-UPS SRT 6 kVA PDU, 208 V (4) L6-20, (1) L6-30
- SRT008: APC Smart-UPS SRT 8/10 kVA PDU, 208 V (6) L6-30
- SRT011: APC Smart-UPS SRT 3 kVA PDU, 208 V (3) L6-30
- SRT012: APC Smart-UPS SRT 2.2/3 kVA input/output HW kit

## Service bypass panels

- SBP1500RM: APC service bypass panel — 120 V; 15 A; BBM; (8) 5-15R
- SBP2200RM: APC service bypass panel — 120 V; 20 A; BBM; (6) 5-15R (2) 5-20R

- SBP3000RM: APC service bypass panel — 120 V; 16 A; BBM; (4) 5-20R (1) L5-30R
- SBP5KRMT2U: APC service bypass panel — 200/208/240 V; 30 A; BBM; L6-30P input; (2) L6-30R (2) L6-20R output
- SBP6KRMT2U: APC service bypass panel — 200/208/240 V; 50 A; MBB; L6-30P/HW input; (1) L6-30R (2) L6-20R output
- SBP10KRMT4U: APC service bypass panel — 200/208/240 V; 100 A; MBB; hardware input; (3) L6-30R (3) L6-20R output

## Step-down transformers

- SRT5KTF: APC Smart-UPS SRT 3/5/6 kVA 3U tower isolation/step-down transformer
- SRT5KRMTF: APC Smart-UPS 3/5/6 kVA 2U RM step-down transformer
- SRT10KRMTF: APC Smart-UPS SRT 10 kVA 4U RM step-down transformer

## Other

- SURT013: SURT equipment cart

## Replacement battery cartridge

- APCRBC140: RBC for SRT 5 kVA —10 kVA UPS
- APCRBC155: RBC for SRT 1-1.5 kVA
- APCRBC141: RBC for SRT 2.2 kVA UPS
- APCRBC152: RBC for SRT 3 kVA UPS

## Runtime estimates at half and full load (minutes)

UPS Half/Full Loads	SRT1000XLA (RM) (RM-NC) 450 W/900 W	SRT1500XLA (RM) (RM-NC) 675 W/1350 W	SRT2200XLA (RM) (RM-NC) 900 W/1800 W	SRT3000XLA (RM) (RM-NC) 1350 W/2700 W	SRT3000XLT (RM) SRT3000XLW-IEC (RM) SRT3000RMXLT-NC 1350 W/2700 W	SRT5KRMXLW-HW 2250 W/4500 W	SRT5KXLT (RM) SRT5KXLT-IEC (RM) 2125 W/4250 W	SRT6KXLT (RM) SRT6KXLT-IEC (RM) 3000 W/6000 W	SRT8KXLT (RM) SRT8KXLT-IEC (RM) 4000 W/8000 W	SRT10KXLT (RM) SRT10KXLT-IEC (RM) 5000 W/10000 W
Internal	25.36/10.48	13.16/4.61	10.3/3.26	10.28/3.21	11.36/3.8	11.75/3.98	10.53/3.8	8.3/2.4	14.4/5.16	11.4/3.73
(1) Battery pack	88/40	50/22.58	41/18.1	37/16	44/19.9	46/20.46	42/19	34/14.86	37/15	27.83/11.5
(2) Battery packs	156/73	91/41	74/33	68/31	80/37	83/38	76/35	62/28.28	54/24.41	45/19.65
(3) Battery packs	226/106	132/61	109/50	99/45	117/54	121/56	112/52	92/42	76/34	62/28.05
(4) Battery packs	299/141	175/82	144/67	132/61	156/73	160/75	148/69	122/56	98/44	81/36



# Smart-UPS On-Line SRT 1000 VA and SRT 1500 VA 120 V

## Technical specifications

Product features	SRT1000XLA - SRT1000RMXLA SRT1000RMXLA-NC (Pre-installed NMC, AP9641)	SRT1500XLA - SRT1500RMXLA SRT1500RMXLA-NC (Pre-installed NMC, AP9641)
<b>Output</b>		
Power rating	1000 VA/900 W	1500 VA/1350 W
Nominal output voltage	120 V	
Output frequency	50/60 Hz $\pm$ 3 Hz (auto sense) 50/60 Hz $\pm$ 0.1 Hz (user selectable)	
Topology	Double-conversion Online	
Online efficiency at full load (typical)	91.5% (ENERGY STAR)	
Green mode efficiency at full load (typical)	97%	
Output connections (switched groups)	(6) NEMA 5-15R	(6) NEMA 5-15R
<b>Input</b>		
Nominal input voltage	120 V	
Input voltage range full load (half load)	80 V – 150 VAC $\pm$ 5V (50 – 150 VAC $\pm$ 5V)	108 V – 150 VAC $\pm$ 5V (50 – 150 VAC $\pm$ 5V)
Input frequency	40 – 70 Hz	
Input connection	5-15P	
<b>Batteries and runtime</b>		
Battery type	Sealed maintenance-free valve regulated lead-acid battery with suspended electrolyte, leak proof	
Typical backup time at 1/2 load (min.)	25.4	13.2
Typical backup time at full load (min.)	10.5	4.6
Replacement battery (quantity)	APCRBC155 (1)	
External battery pack (tower/rackmount)	SRT48BP/SRT48RMBP	
<b>Communication and management</b>		
Interface ports	Serial (RJ45), USB (Type A) and SmartSlot	
Control panel	High resolution graphical LCD display	
Emergency power off (EPO)	Yes (NO/NC connections)	
<b>Physical</b>		
Rack height	3" (85 mm), 2U	
Maximum width (RM)	17" (432 mm)	
Maximum depth (RM)	21.5 inches/545 mm	
Net weight	48.5 lb (22.0 kg)	
<b>Conformance</b>		
Regulatory	UL-1778, FCC Part 15 Class A, CSA	
Warranty	3 years electronics, 2 years battery	

# Smart-UPS On-Line SRT 2200 VA and SRT 3000 VA 120 V

## Technical specifications

Product features	SRT2200XLA - SRT2200RMXLA SRT2200RMXLA-NC (Pre-installed NMC, AP9641)	SRT3000XLA - SRT3000RMXLA SRT3000RMXLA-NC (Pre-installed NMC, AP9641)
<b>Output</b>		
Power rating	2200 VA/1800 W	3000 VA/2700 W
Nominal output voltage	120 V	
Output frequency	50/60 Hz $\pm$ 3 Hz (auto sense) 50/60 Hz $\pm$ 0.1 Hz (user selectable)	
Topology	Double-conversion Online	
Online efficiency at full load (typical)	91.5% (ENERGY STAR)	
Green mode efficiency at full load (typical)	97%	
Output connections (switched groups)	(6) 5-20, (1) L5-20R	(8) 5-20, (1) L5-30R
<b>Input</b>		
Nominal input voltage	120 V	
Input voltage range full load (half load)	108 V – 150 VAC $\pm$ 5V (50 – 150 VAC $\pm$ 5V)	
Input frequency	40 – 70 Hz	
Input connection	5-20P	L5-30P
<b>Batteries and runtime</b>		
Battery type	Sealed maintenance-free valve regulated lead-acid battery with suspended electrolyte, leak proof	
Typical backup time at 1/2 load (min.)	10.3	10.4
Typical backup time at full load (min.)	3.2	3.1
Replacement battery (quantity)	APCRBC141 (1)	APCRBC152 (1)
External battery pack (tower/rackmount)	SRT72BP/SRT72RMBP	SRT96BP/SRT96RMBP
<b>Communication and management</b>		
Interface ports	Serial (RJ45), USB (Type A) and SmartSlot	
Control panel	High resolution graphical LCD display	
Emergency power off (EPO)	Yes (NO/NC connections)	
<b>Physical</b>		
Rack height	3.35" (85 mm), 2U	3.35" (85 mm), 2U
Maximum width (RM)	17" (432 mm)	17" (432 mm)
Maximum depth (RM)	23 " (559 mm)	25 " (636 mm)
Net weight	55 lb (24.95 kg)	69 lb (31.3 kg)
<b>Conformance</b>		
Regulatory	UL-1778, FCC Part 15 Class A, CSA	
Warranty	3 years electronics, 2 years battery	

# Smart-UPS On-Line SRT 3000 VA 208 V

## Technical specifications

Product features	SRT3000XLW-IEC SRT3000RMXLW-IEC	SRT3000XLT - SRT3000RMXLT SRT3000RMXLT-NC (Pre-installed NMC, AP9641)
<b>Output</b>		
Power rating	3000 VA/2700 W	
Nominal output voltage	230 V (208 V, 220 V, 230 V, 240 V user selectable)	208 V (240 V user selectable)
Output frequency	50/60 Hz $\pm$ 3 Hz (auto sense) 50/60 Hz $\pm$ 0.1 Hz (user selectable)	
Topology	Double-conversion Online	
Online efficiency at full load (typical)	91% (ENERGY STAR)	
Green mode efficiency at full load (typical)	97%	
Output connections (switched groups)	(6) IEC 320 C13 (2) IEC 320 C19	(2) L6-20R (1) L6-30R
<b>Input</b>		
Nominal input voltage	230 V (208 V, 220 V, 240 V user selectable)	208 V (240 V user selectable)
Input voltage range full load (half load)	160 – 275 V (100 – 275 V)	
Input frequency	40 – 70 Hz	
Input connection	IEC 60320 C20, Schuko CEE 7/EU1-16P, British BS1363A	L6-20P
<b>Batteries and runtime</b>		
Battery type	Sealed maintenance-free valve regulated lead-acid battery with suspended electrolyte, leak proof	
Typical backup time at 1/2 load (min.)	11.8 min	11.4 min
Typical backup time at full load (min.)	4.0 min	3.8 min
Replacement battery (quantity)	APCRBC152 (1)	
External battery pack (tower/rackmount)	SRT96BP/SRT96RMBP	
<b>Communication and management</b>		
Interface ports	Serial (RJ45), USB (Type A) and SmartSlot	
Control panel	High resolution graphical LCD display	
Emergency power off (EPO)	Yes (NO/NC connections)	
<b>Physical</b>		
Rack height	3.35" (85 mm), 2U	
Maximum width (RM)	17" (432 mm)	
Maximum depth (RM)	25" (636 mm)	
Net weight	69 lb (31 kg)	
<b>Conformance</b>		
Regulatory	CE, VDE, RCM, and EAC, IEC/EN 62040-1, IEC/EN 62040-2, UL-1778, FCC Part 15 Class A, CSA	UL-1778, FCC Part 15 Class A, CSA
Warranty	3 years electronics, 2 years battery	

# Smart-UPS On-Line SRT 3000 VA 120/208 V with Transformer

## Technical specifications

Product features	SRT3000XLT-5KTF	SRT3000RMXLT-5KTF
<b>Output</b>		
Power rating	3000 VA/2700 W	
Nominal output voltage (UPS)	208 V (240 V user selectable)	
Nominal output voltage (transformer)	120 V, 208 V, 240 V	120 V
Output frequency	50/60 Hz $\pm$ 3 Hz (auto sense)	
Output connections (UPS)	(2) L6-20R, (1) L6-30R (for transformer)	(2) L6-20R, (1) L6-30R (for transformer)
Output connections (transformer)	(8) 5-20R, (2) L6-20R, (1) L6-30R, (1) L14-30R	(12) 5-20R
<b>Input</b>		
Nominal input voltage	208 V (240 V user selectable)	
Input connection	L6-20P	
<b>Physical</b>		
Rack height	Tower	6.7" (170 mm) 4U
Maximum width (RM)	8.45" (215 mm)	17" (432 mm)
Maximum depth (RM)	26" (660 mm)	25" (636 mm)
Net weight	194 lb (87.82 kg)	164 lb (74.18 kg)
<b>Conformance</b>		
Regulatory	UL-1778, FCC Part 15 Class A, CSA	
Warranty	3 years electronics, 2 years battery	

\* Transformer must be connected to UPS output with constant input voltage.

# Smart-UPS On-Line SRT 5 kVA and 6 kVA 208 V

## Technical specifications

Product features	SRT5KRMXLW-HW	SRT5KXLT SRT5KRMXLT	SRT5KXLT-IEC SRT5KRMXLT-IEC	SRT6KXLT SRT6KRMXLT	SRT6KXLT-IEC SRT6KRMXLT-IEC
<b>Output</b>					
Power rating	5000 VA/4500 W	208VAC: 5400 VA/4800 W 240VAC: 6000 VA/4800 W		6000 VA/6000 W	
Nominal output voltage	230 V (208, 220, 230, 240 V user selectable)	208 V (240 V user selectable)			
Output frequency	50/60 Hz $\pm$ 3 Hz (auto sense) 50/60 Hz $\pm$ 0.1 Hz (user selectable)				
Topology	Double-conversion Online				
Online efficiency at full load (typical)	94% (ENERGY STAR)				
Green mode efficiency at full load (typical)	98%				
Output connections	HW	(2) L6-20R (2) L6-30R	(6) IEC 320 C13 (4) IEC 320 C19	(2) L6-20R (3) L6-30R, HW	(6) IEC 320 C13 (4) IEC 320 C19, HW
<b>Input</b>					
Nominal input voltage	230 V (208, 220, 230, 240 V user selectable)	208 V (240 V user selectable)			
Input voltage range full load (half load)	160 – 275 V (100 – 275 V)				
Input frequency	40 – 70 Hz				
Input connection	Hardwire 3-wire (L1+L2/N+G)	L6-30P		Hardwire 3-wire (L1+L2+G)	
<b>Batteries and runtime</b>					
Battery type	Sealed maintenance-free valve regulated lead-acid battery with suspended electrolyte, leak proof				
Typical backup time at 1/2 load (min.)	11.75 min.	10.53 min.		8.3 min.	
Typical backup time at full load (min.)	3.98 min.	3.8 min.		2.4 min.	
Replacement battery (quantity)	APCRBC140				
External battery pack (tower/rackmount)	SRT192BP/SRT192RMBP				
<b>Communication and management</b>					
Interface ports	RJ-45 with status LEDs (10/100 Base-T), serial (RJ45), USB (Type B), and SmartSlot				
Control panel	High-resolution graphical LCD display				
Emergency power off (EPO)	Yes (NO/NC connections)				
Embedded network management with environmental monitoring	Yes				
<b>Physical</b>					
Rack height	3 U			4 U	
Maximum height rackmount SKU	5.1" (130 mm)			6.85" (174 mm)	
Maximum width rackmount SKU	17" (432 mm)			17" (432 mm)	
Maximum depth rackmount SKU	28.32" (719 mm)			28.32" (719 mm)	
Net weight	123 lbs (55.8 kg)			135 lbs (61.25 kg)	
<b>Conformance</b>					
Regulatory	CE, VDE, UL-1778, FCC Part 15 Class A, cUL	UL-1778, FCC Part 15 Class A, cUL, NOM			
Warranty	3 years for electronics, 2 years for battery				

# Smart-UPS On-Line SRT 5 kVA and 6 kVA 120/208 V with Transformers

## Technical specifications

Product features	SRT5KXLT-5KTF	SRT5RMKXLT-5KTF	SRT6KXLT-5KTF	SRT6RMKXLT-5KTF
<b>Output</b>				
Power rating	208VAC: 5400 VA/4800 W 240VAC: 6000 VA/4800 W		6,000 VA/6,000 W	
Nominal output voltage	208 V (240 V user selectable)			
Nominal output voltage (transformer)	120 V, 208 V, 240 V	120 V	120 V, 208 V, 240 V	120 V
Output frequency	50/60 Hz $\pm$ 3 Hz (auto sense)			
Output connections (UPS)	(2) L6-20R, (2) L6-30R (1 for transformer)		(2) L6-20R, (2) L6-30R (1 for transformer), HW	
Output connections (transformer)	(8) 5-20R, (2) L6-20R, (1) L6-30R, (1) L14-30R	(12) 5-20R	(8) 5-20R, (2) L6-20R, (1) L6-30R, (1) L14-30R	(12) 5-20R
<b>Input</b>				
Nominal input voltage	208 V (240 V user selectable)			
Input voltage range full load (half load)	160 – 275 V (100 – 275 V)			
Input frequency	40 – 70 Hz			
Input connection	Hardwire 3-wire (L1 + L2/N + G)			
<b>Physical</b>				
Rack height	Tower	5U	Tower	6U
Maximum height	17" (432 mm)	8.6" (219 mm)	17" (432 mm)	10.35" (263 mm)
Maximum width	10.2" (260 mm)	17" (432 mm)	11.95" (304 mm)	17" (432 mm)
Maximum depth	28.32" (719.4 mm)	28.32" (719.4 mm)	28.32" (719.4 mm)	28.32" (719.4 mm)
Net weight	248 lbs (112.62 kg)	218 lbs (98.98 kg)	260 lbs (118.07 kg)	230 lbs (104.43 kg)
<b>Conformance</b>				
Regulatory	UL-1778, FCC Part 15 Class A, cUL			
Warranty	3 years electronics, 2 years battery			

# Smart-UPS On-Line SRT 8 kVA and 10 kVA 208 V

## Technical specifications

Product features	SRT8KXLT SRT8KRMXLT	SRT8KXLT30 SRT8KRMXLT30	SRT8KXLT-IEC SRT8KRMXLT-IEC	SRT10KXLT SRT10KRMXLT	SRT10KXLT30 SRT10KRMXLT30	SRT10KXLT-IEC SRT10KRMXLT-IEC
<b>Output</b>						
Power rating	8,000 VA/8,000 W			10,000 VA/10,000 W		
Nominal output voltage	208 V (240 V user selectable)					
Output frequency	50/60 Hz $\pm$ 3 Hz (auto sense) 50/60 Hz $\pm$ 0.1 Hz (user selectable)					
Topology	Double-conversion Online					
Online efficiency at full load (typical)	94% (ENERGY STAR)			93% (ENERGY STAR)		
Green mode efficiency at full load (typical)	98.5%			99%		
Output connections	(4) L6-20R (2) L6-30R, HW	(6) L6-30R, HW	(6) IEC 320 C13 (4) IEC 320 C19, HW	(4) L6-20R (2) L6-30R, HW	(6) L6-30R, HW	(6) IEC 320 C13 (4) IEC 320 C19, HW
<b>Input</b>						
Nominal input voltage	208 V (240 V user selectable)					
Input voltage range full load (half load)	160 – 275 V (100 – 275 V)					
Input frequency	40 – 70 Hz					
Input connection	Hardwire 3-wire (L1+L2/N+G)					
<b>Batteries and runtime</b>						
Battery type	Sealed maintenance-free valve regulated lead-acid battery with suspended electrolyte, leak proof					
Typical backup time at 1/2 load (min.)	14.4 min.			11.4 min.		
Typical backup time at full load (min.)	5.2 min.			3.7 min.		
Replacement battery (quantity)	APCRBC140 (2)					
External battery pack (tower/rackmount)	SRT192BP2/SRT192RMBP2					
<b>Communication and management</b>						
Interface ports	RJ-45 with status LEDs (10/100 Base-T), serial (RJ45), USB (Type B), and SmartSlot					
Control panel	High-resolution graphical LCD display					
Emergency power off (EPO)	Yes (NO/NC connections)					
Embedded network management with environmental monitoring	Yes					
<b>Physical</b>						
Rack height	6U					
Maximum height rackmount SKU	10.35" (263 mm)					
Maximum width rackmount SKU	17" (432 mm)					
Maximum depth rackmount SKU	28.15" (715 mm)					
Net weight	246 lbs (111.82 kg)					
<b>Conformance</b>						
Regulatory	UL-1778, FCC Part 15 Class A, CSA C22.2 No.107.3-05, NOM					
Warranty	3 years electronics, 2 years battery					

# Smart-UPS On-Line SRT 8 kVA and 10 kVA 120/208 V with Transformers

## Technical specifications

Product features	SRT8KXLT-5KTF	SRT8KRMXLT-5KTF	SRT10KRMXLT-10KTF	SRT10KXLT-5KTF2	SRT10KRMXLT-5KTF2
<b>Output</b>					
Power rating (UPS)	8,000 VA/8,000 W		10,000 VA/10,000 W		
Power rating (transformer)	5000 VA		10 kVA	5000 VA	
Nominal output voltage	208 V (240 V user selectable)				
Nominal output voltage (transformer)	120 V, 208 V, 240 V	120V	120 V, 208 V, 240 V		120 V
Output frequency	50/60 Hz $\pm$ 3 Hz (auto sense)				
Output connections (UPS)	(4) L6-20R, (1) L6-30R (for transformer)		(4) L6-20R, (2) L6-30R	(4) L6-20R, (2) L6-30R, (1) Hardwire 3-wire (2P + E)	(4) L6-20R, (2) L6-30R, (1) Hardwire 3-wire (2P + E)
Output connections (transformer)	(8) 5-20R, (2) L6-20R, (1) L6-30R, (1) L14-30R	(12) 5-20R	(2) L5-20R, (2) L14-30R, (2) Hardwire 3-wire (2P + E), (1) Hardwire 4-wire (2P + N + E)	(16) 5-20R, (4) L6-20R, (2) L6-30R, (2) L14-30R	(24) 5-20R
<b>Input</b>					
Nominal input voltage	208 V (240 V user selectable)				
Input voltage range full load (half load)	160 – 275 V (100 – 275 V)				
Input frequency	40 – 70 Hz				
Input connection	Hardwire 3-wire (L1+L2+G)				
<b>Physical</b>					
Rack height	Tower	8U	10U	Tower	10U
Maximum height	17" (432 mm)	13.85" (352 mm)	17.25" (438 mm)	17" (432 mm)	17.35" (441 mm)
Maximum width	15.45" (393 mm)	17" (432 mm)	17" (432 mm)	20.55" (523 mm)	17" (432 mm)
Maximum depth	28.15" (715 mm)	28.15" (715 mm)	29.5" (749 mm)	28.15" (715 mm)	28.15" (715 mm)
Net weight	371 lbs (168.4 kg)	341 lbs (154.76 kg)	466 lbs (211.58 kg)	496 lbs (225.22 kg)	436 lbs (197.94 kg)
<b>Conformance</b>					
Regulatory	UL-1778, FCC Part 15 Class A, CSA C22.2 No.107.3-05				
Warranty	3 years electronics, 2 years battery				





**Schneider Electric**

One Boston Place Floor 27  
Boston, MA 02108  
United States  
(857)205-9626

[www.apc.com](http://www.apc.com)

September 2022

©2022 Schneider Electric. All Rights Reserved. Schneider Electric | Life Is On, APC, Smart-UPS, PowerChute, and SmartSlot are trademarks and the property of Schneider Electric SE, its subsidiaries, and affiliated companies. All other trademarks are the property of their respective owners.  
998-1257966\_GMA-US\_B

This document has been  
printed on recycled paper

