

**HUBBELL**  
Wiring Device-Kellems

**Locking Devices, Twist-Lock®,  
Industrial, Female Insulgrip®,  
Connector Body, 50A 250V  
DC/600V AC, 3-Pole 4-Wire  
Grounding, Non-NEMA**

By Hubbell Wiring Device-Kellems  
Catalog # [HBL3764C](#)

Locking Devices, Twist-Lock®, Industrial, Female Insulgrip®  
Connector Body, 50A 250V DC/600V AC, 3-Pole 4-Wire  
Grounding, Non-NEMA, Screw Terminal, Nylon housing  
thermoplastic polyester interior, Black



## General

|                              |  |
|------------------------------|--|
| Application                  |  |
| Catalog Number               | HBL3764C   |
| Color                        |  |
| EU RoHS Indicator            | No   |
| Environmental Conditions     | Indoor Dry Unless Protected By Additional Means  |
| Insulation                   | Insulated Body   |
| Item Type                    | 50A Insulgrip® Connector   |
| Material                     | Nylon  |
| Material - Mounting Hardware | Cord Mounted   |
| Number Of Poles              | 3-Pole   |
| Operating Temperature        | Maximum continuous 75°C and minimum -40°C without Impact   |
| Performance                  | Electrical - Current Interrupting - Certified for current interrupting at full rated current<br><br>Electrical - Dielectric Voltage - Withstands 2,000V minimum<br><br>Environmental - Flammability - HB or better<br><br>Environmental - Operating Temperatures - Maximum continuous 75°C minimum - 40°C (w/o impact)<br><br>Mechanical - Terminal Accommodation - #10 AWG - #6 AWG stranded copper wire only |
| Type                         | Connector Body<br><br>Connector Body   |
| UPC                          | 783585236421   |

## Dimensions

|              |                             |
|--------------|-----------------------------|
| Dimensions   | 2.59 in x 2.59 in x 6.50 in |
| Display Size | Standard                    |
| Height       | 6.5 in                      |
| Length       | 2.59 in                     |
| Weight       | 1.05 lb                     |
| Width        | 2.59 in                     |

## Electrical Ratings

|                            |                           |
|----------------------------|---------------------------|
| Amperage Rating            | 50 A                      |
| Connectivity               | Pressure Terminal Screws  |
| Current / Amperage Rating  | 50 A                      |
| Current Rating             | 50 A                      |
| Dielectric Strength        | Withstands 2,000V minimum |
| Voltage Rating             | 250 VDC/600 VAC           |
| Voltage Rating Description | 250 VDC/600 VAC           |

## Conductor Related

|                 |                  |
|-----------------|------------------|
| Cable Range     | 0.830 - 1.250 in |
| Number Of Wires | 4-Wire           |
| Wire Size       | #8 AWG to #4 AWG |

## Certifications And Compliance

|                                    |                              |
|------------------------------------|------------------------------|
| Industry Standard(s)               | Certified to CSA C22.2 No.42 |
|                                    | Listed to UL 498             |
| Standards - RoHS Compliance Status | CM                           |

## Logistics

|                 |      |
|-----------------|------|
| Carton Quantity | 10   |
| Pallet Quantity | 1190 |

## Product Assets

[Catalogs - WDK Catalog Full 2024](#)  
[Warranty - Industrial & Commercial Products](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
WDK\_MX-HBL3764C-SPEC-EN | REV 6/2024