## **Specifications**



Photo is representative





## Eaton LPC235X

Eaton Cooper Power series loadbreak protective cap, 35 kV, Phase to ground: 21.1 kV, AC 1 min: 50.0 kV, DC 15 min: 103.0 kV, BIL: 150.0 kV, Min corona: 26.0 kV, Individual box kit, 200 A, Bag

General specifications	
PRODUCT NAME	Eaton Cooper Power series loadbreak protective cap
CATALOG NUMBER	LPC235X
UPC	194006016339
PRODUCT LENGTH/DEPTH	4 in
PRODUCT HEIGHT	8.3 in
PRODUCT WIDTH	4.2 in
PRODUCT WEIGHT	4.189 lb
COMPLIANCES	Not Applicable
CERTIFICATIONS	IEEE Std 386



Product specifications	
ТҮРЕ	Loadbreak protective cap
STANDARD PACK	Individual box kit
AC 1 MINUTE VOLTAGE WITHSTAND	50.0 kV
BASIC IMPULSE LEVEL	150.0 kV
DC 15 MINUTE WITHSTAND	103.0 kV
CURRENT RATING	200 A
RATING PHASE-TO- GROUND - MAX	21.1 kV
CORONA VOLTAGE LEVEL - MIN	26.0 kV
STANDARD VOLTAGE CLASS	35 kV

Resources	
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - LPC235X
	Line installation and protective

equipment specifiers guide

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



**Eaton Corporation plc** 

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Follow us on social media to get the latest product and support information.

All other trademarks are property of their respective owners.







