



MORTISE LOCKS

The Master Lock® Mortise Lock is the smart keypad upgrade for traditional mortise locks, delivering keyless access for high-traffic entryways in commercial businesses, like retail stores and office buildings. While staff enjoy seamless keyless entry, property owners gain peace of mind with a lock built for durability and enhanced high security. For facility managers, the Mortise Lock integrates effortlessly with smart property systems that utilize open standards like Z-Wave Plus and Zigbee, creating a streamlined, connected access solution across the property.

FEATURES



BUILT-IN HIGH SECURITY

Depend on a pick-resistant lock with durable high security standards for greater resistance to forced attempts. The lock will alarm if forcibly removed.



ULTIMATE CONTROL

Create and manage up to 500 unique codes scheduled for staff and maintenance — temporary or permanent. Always have the option to use the key.



AUTO-LOCK

Ensure the door is locked every time staff closes for the day.



DESIGN VARIETY

Choose from a push button or touchscreen design in a variety of finish options. Expect wear-resistant and long-term durability.



REMOTE ACCESS

Lock doors remotely — access anywhere, anytime.

FLEXIBLE CONNECTIVITY

Connect through Z-Wave Plus and Zigbee and manage with partner apps to expand your smart building and alarm solutions.



MCM614
Keyed Push Button



MCM624
Keyed Touchscreen



MCM634
Key-free Push Button



MCM644
Key-free Touchscreen

WARRANTY & CERTIFICATIONS

ANSI/BHMA	A156.13 Grade 1
UL/CUL	Functions are UL — cUL Fire Listed for use on fire doors having a rating up to and including 3-hours
WARRANTY	2-year electrical warranty; 3-year mechanical and finish warranty
WINDSTORM CERTIFICATION	A250.13 Windstorm

ENVIRONMENTAL

OPERATING TEMPERATURE	-13F (-25C) to 151 F (66C)
HUMIDITY	<85% non-condensation
STORAGE TEMPERATURE	-22F (-30C) to 176F (80C)
IP RATING	IPx5

SPECIFICATIONS

DEADBOLT SPECIFICATIONS	Fits standard residential door
POWER REQUIREMENTS	6 AA alkaline batteries (included) with optional hardwire input for 9V DC external power; 9V battery power backup on keypad.
DOOR THICKNESS	1-3/4", 2", 2-1/4" Door thickness standard
STRIKE	124mm x 32mm x 2.5mm with lip length standard
FACE BORE	2-3/4" x 1-1/8"
EDGE BOREW	2 1/8"
LATCH	1"
BACKSET	3/4" Throw Latch, 1" Deadbolt (optional) 2-3/4" (70MM) standard backset
CYLINDER	Housing for 6-Pin and 7-Pin SFIC, but no cylinder core provided
HANDING	Field Reversible

BASE MODELS



MCM614
Keyed Push Button



MCM624
Keyed Touchscreen



MCM634
Key-free Push Button



MCM644
Key-free Touchscreen

IN THE BOX

- Master Lock® Mortise Lock
- Smart module included*
- Installation Guide
- Screws
- Door Template
- 6 AA Batteries
- 2 Keys

*Included for Z-Wave Plus and Zigbee models

FINISHES



619
Satin Nickel



BSP
Black Suede



OBP
Oil Rubbed Bronze

LEVERS



AU
Augusta



CR
Carmel



PB
Pacific Beach

