Thin Wall Conduit Fittings (for EMT Conduit)

Compression Type Fittings – Zinc Die Cast

COMPRESSION TYPE FITTINGS – ZINC DIE CAST

Features:

- The split compression ring assures solid attachment to the conduit and good ground continuity
- The hex surfaces on the compression nut provide for easy wrenching to quickly and easily tighten the nut
- Concrete tight
- Threadless

Standard Material:

- Zinc

Standard Finish:

- Natural

Straight Connectors – Insulated

UL File No. E-22132



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
1650DC	½"	50	8
1651DC	¾"	25	11
1652DC	1"	15	17
1653DC	1¼"	10	31
1654DC	1½"	10	39
1655DC	2"	5	56
1656DC	2½"	12	93
1657DC	3"	12	120
1658DC	3½"	6	149
1659DC	4"	6	172

Straight Connectors – Non-insulated


UL File No. E-22132



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
650DC	½"	50	8
651DC	¾"	25	11
652DC	1"	15	17
653DC	1¼"	10	31
654DC	1½"	10	39
655DC	2"	5	56
656DC	2½"	12	93
657DC	3"	12	120
658DC	3½"	6	149
659DC	4"	6	172

Couplings

UL File No. E-22132



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
660DC	½"	50	11
661DC	¾"	25	16
662DC	1"	15	22
663DC	1¼"	10	40
664DC	1½"	10	48
665DC	2"	5	64
666DC	2½"	12	124
667DC	3"	12	144
668DC	3½"	6	190
669DC	4"	6	228