

SONANCE

POWERPIPE X SERIES DATA SHEET

PPX10

TECHNICAL SPECIFICATIONS

SKU	93786 - Each
Woofers	10" (254mm) anodized aluminum cone, rubber surround, high excursion
Frequency Response	39Hz - 115Hz +/-3dB
Impedance	4 ohms nominal
Sensitivity (2.83V/1m)	92dB SPL
Enclosure	MDF (Medium Density Fiberboard)
Finish	Textured Black
Recommended Power	400 watts
Recommended Amplifiers	Blaze Powerzone Connect 1502 3004 6008 Sonance DSP 2-750 MKIII
Tube Inside Diameter	4.02" (102mm)
Tube Length	21.65" (550mm)
Product Dims w/ Feet (WxHxD)	12.99" x 13.6" x 11.81" (330mm x 346mm x 300mm)
Product Dims w/o Feet (WxHxD)	12.99" x 12.99" x 11.81" (330mm x 330mm x 300mm)
Product Weight	38.27 lbs. (17.36kg)
Shipping Weight	44.75 lbs. (20.3kg)

ACCESSORIES

PPX-8R | 93796
PPX 8" XPC Grille Connector

PPX-6R | 93795
PPX 6" XPC Grille Connector

PPX-4to6-90-ADAPTER | 93792
PPX 4" to 6" 90-Degree Adapter

PPX-4to6-STR-ADAPTER | 93791
PPX 4" to 6" Straight Adapter

PPX-3.5x16-2-STR | 93790
PPX Straight Toekick Connector and Grille

PPX-3.5x16-2-90 | 93789
PPX 90-Degree Toekick Connector and Grille

PPX TOEKICK REPLACEMENT GRILLE | 93799
Straight or 90-Degree Toekick Connector Required

DIMENSIONAL DRAWINGS

