

FLOOR, WALL & MOSAIC

LAUREL HEIGHTS™
GLAZED PORCELAIN & GLAZED CERAMIC



Photo features Laurel Heights Gray Summit 12 x 24 on the floor and Gray Summit 12 x 18 with 2 x 4 mosaic on the wall.

LAUREL HEIGHTS™ GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAIC WITH REVEAL IMAGING®

A realistic interpretation of refined travertine, Laurel Heights™ features floor, wall, and mosaic combinations, all produced with Reveal Imaging® for exceptional compatibility. A soft-structured surface detail provides both visual and tactile appeal, complemented by high variation for a more natural appearance. The color palette offers a fresh take on traditional neutral colors: Gray Summit, Elevated Beige, Brown Pinnacle and Charcoal Crest.

LAUREL HEIGHTS™

GLAZED PORCELAIN FLOOR TILE



GRAY SUMMIT LH98



ELEVATED BEIGE LH96



BROWN PINNACLE LH97



CHARCOAL CREST LH99

GLAZED CERAMIC WALL TILE



GRAY SUMMIT LH98



ELEVATED BEIGE LH96



BROWN PINNACLE LH97



CHARCOAL CREST LH99

GLAZED CERAMIC MOSAIC



GRAY SUMMIT LH98



ELEVATED BEIGE LH96



BROWN PINNACLE LH97



CHARCOAL CREST LH99



All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.

FLOOR, WALL & MOSAIC



Photo features Laurel Heights™ Gray Summit 12 x 24 on the floor and Gray Summit 12 x 18 with 2 x 4 mosaic on the wall.

LAUREL HEIGHTS™ GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAIC WITH REVEAL IMAGING®

LAUREL HEIGHTS™

SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	18 x 18 Floor Tile	117-3/4" x 17-3/4" (45.20 cm x 45.20 cm)	5/16"	17.60	8
	12 x 24 Floor Tile	11-13/16" x 23-13/16" (30.00 cm x 60.48)	5/16"	15.60	8
	12 x 12 Floor Tile	11-13/16" x 11-13/16" (30.00 cm x 30.00 cm)	5/16"	14.55	15
	12 x 18 Wall Tile 	12" x 18" (30.51 cm x 45.77 cm)	5/16"	16.50	11
	2 x 4 Brick-Joint Mosaic  	12" x 12" Sheet (30.48 cm x 30.48 cm Sheet)	1/4"	9.96	12

TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose 	3 x 12	P-43C9F	22
	Wall Bullnose (12" side) 	3 x 12	S-43C9W	22
	Wall Bullnose Corner 	3 x 3	SN-4310	32

 Ceramic body  Dot-mounted

INSTALLATION & PRICING

RECOMMENDED GROUT JOINT:

Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length of 15" or greater in a staggered brick-joint pattern.)

Wall: 1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%.)

Mosaic: 1/8"

RELATIVE PRICING: Medium

SHADE VARIATION



PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT	WALL RESULT	MOSAIC RESULT
Water Absorption	C373	< 0.5%	< 20.0%	< 3.0%
Breaking Strength	C648	> 275 lbs.	120 - 230 lbs.	> 250 lbs.
Scratch Hardness	MOHS	8.0	4.0 - 6.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant
Abrasion Resistance	C1027	4	N/A	4

For additional information on test results, visit us at: americanolean.com/information/TestResults.

USAGE

FLOORS	WALLS	COUNTERTOPS
F	W	C

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●*
Wet & Level – Interior Floor	≥ 0.42	●*
Shower Floors (Residential or Light Commercial)	≥ 0.42	●**
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●*
Pool Linings	N/A	●**

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Floor tile suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

Wall and mosaic tile suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

* Wall tile not suitable for this application

** Mosaic tile only

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit americanolean.com.



All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.

AMERICANOLEAN.COM