



### TECHNICAL INFORMATION



V2 Slight Variation



Import Stock



Recommend offset pattern  $\leq 33\%$



PEI Rating 4-5



DCOF:  $\geq 0.42$



Frost Resistant



Water Absorption:  $\leq 0.1\%$



Made in Italy

## COLORS



In Ivory  
CER ICII



Contro Ivory  
CER ICCI



In Cream  
CER ICIC



Contro Cream  
CER ICCC



Contro Grey  
CER ICCG




In Grey  
CER ICIG

## MOSAIC




In Ivory  
CER ICII HEX



Contro Ivory  
CER ICCI HEX



In Cream  
CER ICIC HEX



Contro Cream  
CER ICCC HEX



Contro Grey  
CER ICCG HEX



In Grey  
CER ICIG HEX



In Ivory  
CER ICII MOS22



Contro Ivory  
CER ICCI MOS22



In Cream  
CER ICIC MOS22



Contro Cream  
CER ICCC MOS22



Contro Grey  
CER ICCG MOS22



In Grey  
CER ICIG MOS22

## DECORATIVE



In Ivory  
CER ICII LINES



In Cream  
CER ICIC LINES



In Grey  
CER ICIG LINES

## Mosaic and Deco

11" x 13" x 9.5mm Hexagon Mosaic  
Rectified Matte  
2" x 2" x 9.5mm Mosaic  
Rectified Matte  
24" x 48" x 9.5mm Lines Decorative  
Rectified Matte

## Field

48" x 48" x 9.5mm Rectified  
40" x 40" x 8.5mm Rectified  
Matte, R11 & Tile Wax  
24" x 48" x 9.5mm Rectified- **STOCK**  
Matte & Tile Wax  
24" x 24" x 9.5mm Rectified  
Matte, R11 & Tile Wax  
12" x 24" x 9.5mm Rectified- **STOCK**  
Matte & R11



### Tiles, Mosaic and Trim\*

SIZE	ACTUAL	THICKNESS	FINISH
48" x 48" Rectified	47.24" x 47.24"	9.5mm	Matte/Natural
40" x 40" Rectified	39.37" x 39.37"	8.5mm	Matte/Natural R11 Tile Wax
24" x 48" Rectified	23.62" x 47.24"	9.5mm	Matte/Natural Tile Wax
24" x 24" Rectified	23.62" x 23.62"	9.5mm	Matte/Natural R11 Tile Wax
12" x 24" Rectified	11.81" x 23.62"	9.5mm	Matte/Natural R11
24" x 48" Lines Decorative Rectified	23.62" x 47.24"	9.5mm	Matte/Natural
11" x 13" Hexagon Mosaic Rectified	11.02" x 12.59"	9.5mm	Matte/Natural
2" x 2" Mosaic Rectified	11.81" x 11.81"	9.5mm	Matte/Natural
3" x 24" Bullnose Rectified	2.55" x 243.62"	9.5mm	N/A

\* Not all sizes are available in all colors and finishes.

### Performance Characteristics

Breaking Strength	≥ 1300N
Chemical Resistance	A-HA-LA
DCOF	≥ 0.42
Deep Scratch Resistance - Unglazed	N/A
Frost Resistance	Resistant
Mohs Hardness - EN101	6
Water Absorption	≤ 0.1%
Certifications	N/A
Country of Origin	Italy
Shade Variation Code	V2

### Application\*\*

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	•

\*\* These recommendations are not defined by ANSI Standards

