

Product Name: OS-55A

Regulatory Information:

un 1H2/X300/S
 - with 14 gauge bolt
 lockband
 (Test Report P251)

un 1H2/Y250/S
 (Test Report P252)

Bill of Materials:

Body:
 OS-55A, extrusion blow
 molded high molecular
 weight high density
 polyethylene
 (HMW-HDPE)

Cover:
 Plain, one 2" opening,
 or two 2" openings
 available, NPS bungs,
 HDPE.
 Vented bungs are
 available as an option.
 (NPS = National Pipe
 Straight thread)

Lockband:
 Side lever (SLL) or Bolt

Product Illustration:



Nominal Capacity: 55.0 U.S. Gallons	Outage: 2.7 U.S. Gallons	Opening I.D.: 19.3 inches	Total Weight: 24.3 lbs.
Actual Capacity: 57.7 U.S. Gallons	Outage %: 5.0 %	Nominal O.D.: 23.2 inches	Body Weight: 19.6 lbs.
Export Cubes: 11.02 cu. ft.	Overall Height: 36.8 inches	Min. Wall Thickness: 0.090 inches	Chime Height: 0.480 inches
Min. Blocking Diameter: 22.2 inches	Body Height: 36.5 inches	Mid Panel Height: 11.5 inches	

Special Notes:

- 1) Maximum filling temperature 150 F. When filled at this recommended maximum filling temperature drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability.
- 2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 1300 lbs. each. Pallets should be of good quality that provides adequate support for plastic drums.
- 3) Handle with parrotbeak, side grabber, and sling.
- 4) Recycle symbol embossed on bottom.
- 5) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG20384

DESCRIPTION:

55 Gallon HDPE OH Drum, UN Rated