WORKSHOP®MD

WET/DRY VACS

6.5 PEAK HP

16 US GALLON

- Stainless Steel Drum Construction Cleans Up Easily For A Professional Appearance
- Qwik Lock® Filter Fastening System For Easy Filter Changes
- Ergonomic Handle And Large Rear Wheels Transport Easily Over Rough Terrain And Stairs
- Easy To Reach Storage Bag Keeps Accessories Close At Hand
- Dual-Flex® Locking Hose Offers 180° Flexibility At Both Hose Ends For Better Maneuverability
- Integral Blowing Port For Added Versatility

STAINLESS STEEL CART VAC

Featuring a Stainless Steel drum and rough terrain cart, this vac out performs under the toughest of conditions.



2½" DIAMETER







Includes: Vac, Hose, Utility Nozzle, Crevice Tool, Car Nozzle, Wet Nozzle, 2 Extension Wands, Fine Dust Filter, Dust Bag, Owner's Manual

WSI600SS

5 YEAR* LIMITED WARRANTY

WORKSHOP® MD
WET/DRY VACS

6.5 PEAK HP

16 US GALLON

SPECIFICATIONS

Drum Size	16 Gal / 60 L
Peak H.P.	6.5
Voltage	120
Amps	12.0
CFM	181
Static Lift	45 in
Max Air Watts	280
Blowing Capability	Yes
Cord Length	20' / 3 m
Hose Length	7' / 2,1 m
Drain Port	Yes
Construction	Polypropylene
Accessory Size	2½" / 6,4 cm
Accessory Storage	Yes - Bag
U.L. Listed	Yes
Fine Dust Filter	WS22200F
Dust Collection Bag	WS32200F

OPTIONAL FILTRATION

Standard Filter	WS21200F
HEPA Media Filter	WS23200F
Wet Application Filter	WS24200F

QWIK LOCK® MD

Qwik Lock® Filter Fastening System – Makes installing or removing your filter quick, easy and secure.

c UL us LISTED

20'/6M

Large carrying handle provides easy transport.

Easy reach accessory storage keeps accessories close at hand.

Convenient cord wrap.

Easy access power switch for quick operation.

Cart handle with accessory storage improves vac mobility.

Blowing port for added versatility.

dual-flex® LOCKING HOSE

2½" x 7' Dual-Flex® Locking Hose offers 180° flexibility at both hose ends for better maneuverability.

Large rear wheels provide mobility up steps, over thresholds, and rough terrain.

Stainless steel drum – high quality, rugged construction.

Large drain located at the drum's lowest point for quick and easy liquid disposal.





Emerson Tool Company
12969 Manchester Road
St. Louis, MO 63131

1-888-455-8724

WORKSHOPbrand YouTube

Real-world performance data achieved from testing at the end of the hose. Competitors typically test at or near motor. Gallons indicated reflect drum volume, not necessarily collection capacity. Actual capacity dependent upon type of debris collected, condition of filter, and other factors. Peak Horsepower represents a level at or below the maximum horsepower output of an electric motor tested in a laboratory using a dynamometer. All details subject to change without notice.