

SKG-IKOB PRODUCTCERTIFICATE

527.312.26

Date of issue: 23-10-2025



Certificate holder

Cisa SpA
Via Oberdan, 42
IT-48018 Faenza (RA)
T: +39 0546 677 111
E: cisa.safety@allegion.com
I: www.cisa.com



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

euro profile cylinder with non lockable knob

delivered under logo / brand:

CISA

delivered under type- and / or article number:

Astral Tekno iNovate series: 0T317-07-0-12-00

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A blue ink handwritten signature, appearing to be "H.A.J. van Dartel", written over a light blue horizontal line.

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

CERTIFICATE

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

SKG-IKOB PRODUCTCERTIFICATE

Cisa SpA
Number: 527.312.26

page 2 of 2

1. PRODUCT

euro profile cylinder with non lockable knob

PRODUCT TYPE

cylinder

2. TECHNICAL SPECIFICATION

Operating: Mechanical operation
Construction: double, with turn knob
System: horizontal key channel
1 row of 6 mechanically operated pin pairs + 1 row of at least 4 key blocking rings and
1 row of at least 6 passive pins, 1 of them is an active pin
Material: cylinder body: brass with various coatings
Dimension: 17 mm profile from:
30/30 mm in various extensions of 5 mm
Fixing: 1 steel bolt M5, length \geq backset + 10 mm
Intended use: in combination with cylinder mortice locks and security furniture.
Pay Attention!
This cylinder achieves only the SKG-star rating if a door element (including side window),
wherein at least P4A glass has been applied, OR in a door element (including side window)
with a section filling without a view on the knob.
A wooden door element (including side window) with a view to the "standard" turning knob,
should be provided with a SKG (V) certified anti-drill / manipulation device

3. DELIVERY

The preconditions for correct installation and the fasteners to be used are described in the enclosed or digitally published installation instructions with the following version:
0.892.0341.0.00.00-D

4. PERFORMANCES

A euro profile cylinder with non lockable knob according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this euro profile cylinder with non lockable knob is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 2 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this euro profile cylinder with non lockable knob is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).
