

WAC LIGHTING

7"/11"/15" Round

Ceiling and Wall Mount

Fixture Type: _____
 Catalog Number: _____
 Project: _____
 Location: _____

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
<input type="radio"/> FM-07RN 7"	<input type="radio"/> 930 3000K - 90	15W	1100	<input type="radio"/> BK Black
<input type="radio"/> FM-11RN 11"	<input type="radio"/> 935 3500K - 90	15W	1100	<input type="radio"/> BN Brushed Nickel
<input type="radio"/> FM-15RN 15"	<input type="radio"/> 930 3000K - 90	20W	1525	<input type="radio"/> BZ Bronze
	<input type="radio"/> 935 3500K - 90	20W	1525	<input type="radio"/> WT White
	<input type="radio"/> 930 3000K - 90	28W	2550	
	<input type="radio"/> 935 3500K - 90	28W	2550	

Example: **FM-07RN-930-BK**

FEATURES

- Multiple LED array for uniform illumination
- Driver installed within the Junction Box, driver dimension: 2.25" dia x 1" deep
- 5 year warranty

SPECIFICATIONS

Construction	Aluminum with translucent diffuser
Power:	15W, 20W, 28W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED
Lens:	Translucent acrylic diffuser
Rated Life:	50,000 Hours
Mounting:	Installs over a 3", 4" or 3/0-4/0 hybrid junction box, Can be mounted on ceiling or wall in all orientations
Finish:	Electrostatically Powder Coated: Bronze, White, Black, Electroplated Brushed Nickel
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Damp Location Listed, Energy Star 2.0, ADA, Title 24 JA8 Compliant



FINISHES:



LINE DRAWING:

