

GoBoard® FX™ Drain Riser and Grate



For use in GoBoard Point Drain Body

Johns Manville proudly partners with drain system manufacturer FloFX™ to produce the GoBoard® FX™ Designer Series drain riser. The low visibility grout rim offers a clean finish and provides for fine tuning of the grout elevation. The temporary drain grate install plate keeps your project moving along while you select a grate design and finish.



Complies with:
ASME A112.18.2/CSA B125.2
IAPMO PS-106

APPROVED MATERIALS

Substrate - Level wood subfloor, or level concrete slab

Bonding - Polymer modified thin-set mortar compliant with ANSI A118.4 and dry-set mortar compliant with ANSI A118.1.

Joint Sealing - GoBoard® Pro Sealant, GoBoard® Sealant, or approved alternative.

Tools Needed - Utility knife, pencil or pen, straight edge, speed square, level, measuring tape, 90° putty knife, 1/4-in x 1/4-in square-notch, 3/16-in x 5/32-in v-notch trowel, margin trowel, caulk gun, corded or cordless drill, thin-set mixing paddle and bucket.

SAFETY

Please wear gloves, safety glasses, long sleeve shirts, and long pants when installing GoBoard products. Temporary mechanical abrasion (itching) of skin, eyes and respiratory track may occur upon exposures to fibers or dust during handling of GoBoard.



FOLLOW US!



Download the complete installation instructions:
www.JM.com/GoBoard

USES

For use in shower pan areas as a component of the GoBoard Point Drain Body, for the GoBoard Shower System.



FEATURES

Complies to IAPMO PS 106, Tileable Shower Receptors and Shower Kits, and ASME A112.18.2/CSA B125.2. GoBoard Point Drain Kit includes a universal drain body and friction fit universal drain cover riser, and is designed for use with the GoBoard Shower System.

- Low profile design
- Adjustable riser height
- Integrated waterproofing membrane

TECHNICAL DATA

Drain Assembly	Component Spec
Drain Cover	3.9" x 3.9"
Drain Riser	4" x 4"
Clamping Collar	6.5" x 6.5"
Membrane	11" x 11"
PVC Drain Body	2" PVC S40