

Eaton LE215DD06NUX

Catalog Number: LE215DD06NUX

Eaton Cooper Power series loadbreak elbow, Northeast Utilities, Std V:15 kV, Max phase-to-ground:8.3 kV, AC 1 min:34 kV, DC 15 min:34 kV, Impulse:95 kV, Max corona:11 kV, Test:No, 0.89 inch, 1.22 inch, 22.6 mm, 30.0 mm, 1/0 AWG, 2/0 AWG



General specifications

Product Name	Catalog Number
Eaton Cooper Power series loadbreak elbow	LE215DD06NUX
	UPC
	194006005234
Product Length/Depth	Product Height
10 in	3.75 in
Product Width	Product Weight
9 in	3.131 lb
Compliances	Certifications
Not Applicable	IEEE 386

defaultTaxonomyAttributeLabel	Resources
<p>Special features</p> <p>Northeast Utilities</p> <p>Type</p> <p>Loadbreak elbow</p> <p>AC 1 minute voltage withstand</p> <p>34 kV</p> <p>Basic impulse level</p> <p>95 kV</p> <p>Cable insulation diameter - max</p> <p>1.22 in</p> <p>Cable insulation diameter - min</p> <p>0.89 in</p> <p>Solid or compact conductor size</p> <p>2/0 AWG</p> <p>Stranded or compressed conductor size</p> <p>1/0 AWG</p> <p>Current rating</p> <p>200 A</p> <p>DC 15 minute withstand</p> <p>34 kV</p> <p>Maximum rating phase-to-ground</p> <p>8.3 kV</p> <p>Corona voltage level - min</p> <p>11 kV</p> <p>Standard pack</p> <p>Single</p> <p>Standard voltage class</p> <p>15 kV</p> <p>Features</p> <p>Flex Center</p>	<p>Specifications and datasheets</p> <p>Eaton Specification Sheet - LE215DD06NUX</p> <p>Line installation and protective equipment specifiers guide</p>



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia