



## S-100HSG

2 Piece, Full Port, Solder x Hose Connection with Cap and Chain, Stainless Steel Trim, 600 WOG



PART NUMBER	SIZE	CASE	CARTON	WEIGHT
100-663G	1/2" x 3/4" Hose	100	10	46
100-664G	3/4" x 3/4" Hose	60	10	75

- Dezincification Resistant Brass Alloy
- Gland Follower and Single O-Ring Stem Design
- Blow-Out Proof Stem
- Cap and Chain for Easy Drain and Hose Connection
- Heavy Steel Chain
- 100% Leak Tested
- IAPMO Certified - NSF 61 & NSF 372 & NSF 14
- Wetted Surfaces Contain Less than .25% Lead Content



## P-100HPG

2 Piece, Full Port, Press x Hose Connection with Cap and Chain, Stainless Steel Trim, 250 WOG



PART NUMBER	SIZE	CASE	CARTON	WEIGHT
100-673G	1/2" x 3/4" Hose	100	10	60
100-674G	3/4" x 3/4" Hose	100	10	60

- Dezincification Resistant Brass Alloy
- Gland Follower and Single O-Ring Stem Design
- Cap and Chain for Easy Drain and Hose Connection
- Heavy Steel Chain
- Blow-Out Proof Stem
- 100% Leak Tested
- IAPMO Certified - NSF 61 & NSF 372 & NSF 14
- Wetted Surfaces Contain Less than .25% Lead Content



## Lead Free Add-a-Valve

Emergency Shut Off Device



PART NUMBER	SIZE	WEIGHT
800-103ADDG	1/2"	3
800-104ADDG	3/4"	5
800-105ADDG	1"	7
800-106ADDG	1-1/4"	12
800-107ADDG	1-1/2"	16
800-108ADDG	2"	23

- Dezincification Resistant Brass Alloy
- Eliminates Facility Shutdowns
- Cuts Through Copper Tubing with a Hardened Steel Stem Cutter
- Expands a Viton® Seal Across Cut to Stop Flow
- No Pipe Freezing, No Bulky Nitrogen Tanks, No Complete Shutdown
- Bottom Cleanout Cap Serves as Line Tap
- Lead Free Sweat Ball Valve Included in Package
- Loc-Tite® Gasket Sealant Included
- U.S. and Canadian Patent No. 5,316,037
- Can be Installed on Potable Hot/Cold Water and Water/Glycol Systems
- IAPMO Certified - NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content

