TECHNICAL DATA

Capacity under lid	19lt / 5gal		
Lid	LRT1922 - Tear Strip Lid		
Wall Thickness	Lid LRT1922	2.03mm	0.080in
Weight (approx.)	Lid LRT1922	246g	8.67oz
Material	HDPE		
Thermal range	-18°C (0°F) to 66°C (150°F)		
Lid Colour	Standard in White, other colors available.		

PRODUCT CODE

LID: LRT1922



DIMENSIONS	CM	INCHES
Pail Height with Lid	37.08	14.60
Upper width with Lid	31.75	12.15

PACKAGING OF EMPTY LIDS

Warehousing of Lids:

- 300 per tray - 600 per pallet
  SLR3: 1200 per pallet
- Max 4 pallets high for warehousing of lids

TOP LOADING RESISTANCE

60kg (132lbs) at 23°C (73°F), 30 days, product temperature when filling pails and warehouse temperature will affect pail performance. Hofmann recommends testing prior to full production.

OPENING & CLOSING

TO OPEN: Remove tear strip, then lift cover.
TO CLOSE: Place lid on pail, press on with hands or use a rubber mallet.

RECOMMENDATIONS

Do not exceed pallet edges with pails. Grade A pallets should be used with boards that have tight spacing to ensure proper pail support. To improve stability, release air from pail when applying the lid. Stretch wrapping machine tension should be adjusted to ensure no deformation of the pail. Use slip-sheet to improve pails stability. Hofmann recommends testing prior to full production.

APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada regulations.

Handling conditions vary a lot from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm this data.

DISCLAIMER
THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY: Pipeline Packaging

REF NO.: DWG31719

DESCRIPTION:
3.5 - 6.0 Gallon HDPE Cover, Tear Tab, EPDM Gasket with Plastic Spout