annes

BY SONANCE


SPL3 LCR SOUNDBAR DATA SHEET

SPL3 LCR TECHNICAL SPECIFICATIONS

	SPL3 LCR
UOM	Each
Tweeter	0.75" (19mm) Aluminum
Woofer	3" (76mm) High Excursion
Frequency Response	70Hz-24kHz +/-3dB
Impedance	4 ohms (woofer quantity dependent)
Power Handling (RMS)	5 watts minimum; 150 watts maximum
Sensitivity (2.83V/1m)	89dB SPL
Enclosure	Aircraft Grade Aluminum
Width (W)	74.5" (1892.3mm)
Dims (Depth x H)	4.182" x 7.125" (106.22mm x 180.97mm)
Required Depth (D)	3.962" (100.63mm)
Grille Height (H)	7.25" (184.15mm)



4.182 (106.22mm) Depth Side View



74.5" (1892.3mm) Width Front View

SPL3 LCR FEATURES

- Paintable grille available by request only
- LCR format of this bar features two individual systems to provide left, right, and center channels
- Through-hole mount, TV mount, or wall mount options, mounting brackets sold separately
- Available in standard or marine grade

LIMITED FIVE (5) YEAR WARRANTY Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the period stated above. Sonance will at its option and expense during the warranty period, either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. For more details please refer to the product manual.

©2024 Sonance. All rights reserved. Sonance is a registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at www.sonance.com.

JAMES by SONANCE • 2185 Park Place • Minden, NV 89423 • USA • PHONE: (775) 461-7500 • www.jamesloudspeaker.com