CyberPower

P604TRC1 HOME OFFICE SURGE PROTECTION

Protect home and office computers, electronics, and home theater equipment

The CyberPower Home Office Surge Protector P604TRC1 prevents spikes in energy caused by storms and electrical power surges from reaching your home office equipment such as laptops, small electronics, and chargers. The P604TRC1 provides 1,500 joules of protection, 6 outlets and a power cord (4 ft.) with a right-angle plug. It also has data line protection for phone/fax/modem (RJ11).

Features of the P604TRC1 include automatic shutdown, an On/Off switch with integrated 15-Amp circuit breaker, an EMI/RFI Noise filter, keyhole slots, and damage-resistant construction. This surge suppressor comes with a Limited Lifetime Warranty and a \$100,000 Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Consumer Electronics

FEATURES

- Surge suppression: 1,500 J
- Volts: 125 V
- Circuit breaker: 15 A
- Outlet type: 6 NEMA 5-15R surge-protected
- Plug type: Right angle, 45°, NEMA 5-15P
- Power cord: 4 ft
- Data line protection: Phone/fax/modem (RJ11)
- · Color: White
- EMI/RFI Filtration: Yes
- Connected Equipment Guarantee: \$100,000
- Warranty: Limited Lifetime



SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	4 ft (1.2 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Right Angle - 45° Offset
OUTPUT	
Outlet Type	6 - NEMA 5-15R
Outlets - Total	6

SURGE PROTECTION & FILTERING	
Attenuation	32 dB
Clamping Voltage	400V (H-N, H-G, N-G)
Coax Protection RG6	None
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	60,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	30,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Phone Protection RJ11	1-In / 1-Out
Response Time	<1 Nanosecond
Surge Suppression (Joules)	1,500 J

P604TRC1 HOME OFFICE SURGE PROTECTION

SPECIFICATIONS CONT.

PHYSICAL	
Color	White
Material of Construction	Plastic
Safety Covers	No
PHYSICAL DIMENSIONS	
Physical Dimensions - WxHxD (cm)	4.57 x 3.05 x 21.34 cm
Physical Dimensions - WxHxD (mm)	46 x 30 x 213 mm
Physical Dimensions - WxHxD (in.)	1.8 x 1.2 x 8.4 in.
Weight (kg)	0.39 kg
Weight (lb)	0.85 lbs.

SHIPPING DIMENSIONS		
Shipping Dimensions - WxHxD (cm)	10.31 x 31.75 x 3.56 cm	
Shipping Dimensions - WxHxD (mm)	103.12 x 317.5 x 35.56 mm	
Shipping Dimensions - WxHxD (in)	4.06 x 12.5 x 1.4 in.	
Weight (kg)	0.45 kg	
Weight (lb)	1.00 lbs.	
CERTIFICATIONS		
Environmental	RoHS Compliant	
Safety	UL1449 3rd Edition cUL	
WARRANTY		
CEG Amount	\$100,000	
Connected Equipment Guarantee	Lifetime	
Product Warranty	Limited Lifetime Warranty	