

The Building Blocks™ Wood line provides the warmth and sophistication of wood in a durable porcelain tile. Designed to blend perfectly with other Building Blocks™ products, this line provides a stylized re-creation of natural elements that create a harmonious blend of textures and sizes.

# BUILDING BLOCKS™ WOOD | OAK

*Glazed Porcelain*






- FLOOR / WALL 
- RESIDENTIAL 
- COMMERCIAL 
- INDOOR 
- OUTDOOR 
- POOL 



White



Sand

Sizes Thickness Faces Finish Edge Grout Joint Recommendation							
	8" x 47" 7.76" x 46.89"						
	10mm						
	40						
	Matte						
	Rectified						
3/16"							
Testing	Abrasion Resistance C1027	Breaking Strength C648	Chemical Resistance C650	Water Absorption C373	DCOF ANSI A1371	Scratch Hardness MOHS	Shade Variation Rating
Results*	III (Gray & Sand) IV (White)	>500 lbf	Resistant	<0.50%	>0.42	6	V2

**Product and Installation Details | ANSI A108.02**  
 Section 4.3.8.2 - For running bond/brick jointing patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.



- Sustainability Attributes**
- Red List Free
  - Health Product Declaration (HPD) provided upon request
  - Product Packaging is 100% recyclable
  - VOC Free



\*For more information visit [www.emser.com](http://www.emser.com). Always consult a professional for proper usage and installation.