

## PRODUCT SPECIFICATIONS

12-2C

<b>Description:</b>	12/2 High Strand Audio Cable, unshielded with an Overall PVC Jacket
<b>Ratings/Approvals:</b>	NEC Article 725, UL Subject 13, Type CL3, (ETL)US, C(ETL) FT4, RoHS Compliant
<b>Applications:</b>	Intercom Systems, Security Systems, Sound and Audio, Background Music, and Power-Limited Control Circuits. Indoor Applications

---

### CONSTRUCTION

Conductor:	12 AWG Bare Copper (OF)
Stranding:	105 x 32
Insulation Material:	Polyvinyl Chloride
Insulation Thickness:	0.015 in. (0.381 mm.) Nominal
Number of Conductors or Pairs:	2Conductor
Shield:	N/A
Drain:	N/A
Jacket Material:	Polyvinyl Chloride
Jacket Thickness:	0.020 in. (0.508 mm.) Nominal
Overall Cable Diameter:	0.280 in. (7.112 mm.) Nominal
Approx Cable Weight /1,000 ft.:	65 lbs.

---

### ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage:	150 V, RMS
Insulation Colors:	Black, Red
Temperature Rating:	-20°C to +75°C