

Everett



Colors



White
VTL EVWH



Beige
VTL EVBG



Light Gray
VTL EVLG




Dark Gray
VTL EVDG


Sizes



24" x 48" x 9mm Rectified



24" x 24" x 9mm
Rectified



12" x 24" x 9mm
Rectified



6" x 24" x 9mm
Rectified

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
24" x 47" Rectified	23.63" x 47.25"	9.00mm	Matte/Natural
24" x 24" Rectified	23.63" x 23.63"	9.00mm	Matte/Natural
12" x 24" Rectified	11.81" x 23.63"	9.00mm	Matte/Natural
6" x 24" Rectified	5.88" x 23.63"	9.00mm	Matte/Natural
* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.			

Mosaics & Coordinating Trims*

SIZE	ACTUAL	FINISH
12" x 12" Decorative	11.81" x 11.81"	Matte/Natural
2" x 2" Mosaic	11.81" x 11.81"	Matte/Natural
3" x 24" Bullnose Rectified	3.00" x 24.00"	Matte/Natural
6" x 12" Covebase Rectified	5.88" x 11.81"	Matte/Natural
Recommended Grout Joint: 1/8" - Rectified 3/16" - Non Rectified		

Product Characteristics

MATTE/NATURAL	
Breaking Strength (ASTM C648 or ISO 10545-4)	≥ 400 lbs
Chemical Resistance (ASTM C650 or ISO 10545-13)	Resistant
DCOF	> 0.42
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	Resistant
Mohs Hardness - EN101	N/A
Water Absorption (ASTM C373 or ISO 10545-3)	≤ 0.5%
Certifications	HPD LEED Certified
Country of Origin	USA
Shade Variation Code	V2

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	

** These recommendations are not defined by ANSI Standards

Material

Glazed Color-Body Porcelain



Made in USA



Stock and Import



V2 Slight Variation



DCOF: >0.42



HPD and LEED Certified



Scan QR Code for
Product Information and
Installation Images

Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com

