

HOM115CAFI

Mini circuit breaker, Homeline, 15A, 1 pole,
120VAC, 10kA AIR, combo arc fault, pigtail
neutral, plug in, UL

Main

Product	Miniature circuit-breaker
Range	Homeline
Current Rating	15 A
Certifications	UL Listed
Voltage Rating	120 V AC
Mounting Type	Plug-in
Number of Poles	1P
Short Circuit Current Rating	10 kA
Number of Spaces	1
Circuit Breaker Type	Combination ARC-fault
Ratings	HACR rated
Electrical Connection	Screw clamp terminals
Wire Size	1 x AWG 14...AWG 8 (aluminium/copper)

Complementary

Connections - Terminals	Pigtail neutral
Tightening torque	35.4 lbf.in (4.0 N.m) 0.004...0.009 in ² (2.5...6 mm ²) (AWG 14...AWG 8)
Height	3.13 in (79.50 mm)
Width	1 in (25.4 mm)
Depth	2.98 in (75.69 mm)

Environment

Ambient Air Temperature for Operation	104 °F (40 °C)
---------------------------------------	----------------

Ordering and shipping details

Category	US1DE3D06301
Discount Schedule	DE3D
GTIN	785901439721
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.30 in (3.302 cm)
Package 1 Width	4.00 in (10.16 cm)
Package 1 Length	5.50 in (13.97 cm)
Package 1 Weight	10.400 oz (294.835 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	38
Package 2 Height	3.90 in (9.906 cm)
Package 2 Width	13.90 in (35.306 cm)
Package 2 Length	20.80 in (52.832 cm)
Package 2 Weight	24.851 lb(US) (11.272 kg)

Offer Sustainability

Packaging without single use plastic	Yes
Packaging made with recycled cardboard	No
California proposition 65	"WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov "
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Halogen content performance	Halogen free product
Take-back	No
Carbon footprint (kg CO2 eq, Total Life cycle)	41

Contractual warranty

Warranty	Lifetime
----------	----------