

SJEOOW/SJTOOW - 300V - Portable Cord

Type SJEOOW/SJTOOW
105°C - 300 Volt

Flexible and Portable Cord



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Fully annealed stranded bare copper per ASTM B-174

Category Insulation Description:

- Thermoplastic Elastomer

Category Jacket Description:

- Thermoplastic Elastomer, black, white, or yellow Temperature range: -50°C to 105°C

Applications:

- Indoor applications for:
- Portable power tools
- Industrial and consumer lighting fixtures
- Office equipment power supplies
- Construction site power
- Industrial floor care equipment

Standards:

- UL and c(UL) Flexible Cord
- RoHS Compliant

PART NUMBER TABLE						
Part#	Gauge	Conductors	Stranding	Insulation Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
BEJ1802	18	2	16/30	0.03	0.293	45
BEJ1803	18	3	16/30	0.03	0.31	50
BEJ1804	18	4	16/30	0.03	0.34	75
BEJ1602	16	2	26/30	0.03	0.319	55
BEJ1603	16	3	26/30	0.03	0.338	70
BEJ1604	16	4	26/30	0.03	0.372	85
BEJ1402	14	2	41/30	0.03	0.351	70
BEJ1403	14	3	41/30	0.03	0.372	85
BEJ1404	14	4	41/30	0.03	0.409	100
BEJ1202	12	2	65/30	0.03	0.419	90
BEJ1203	12	3	65/30	0.03	0.443	115
BEJ1204	12	4	65/30	0.03	0.486	145

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com
 Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •
 Seattle • St. Louis • Tampa • Toronto
 © 2020 Omni Cable LLC