

CyberPower

MP1055WSS SURGE PROTECTOR MULTI-PACK SOLUTION



Save your devices and money with a four-pack of surge protectors.

The Cyberpower Surge Protector MP1055WSS combo pack comes with two seven-outlet surge protector strips, and two six-outlet swiveling wall tap surge protectors. Each surge protector in this combo pack provides 1200 joules of protection to prevent damaging power spikes and surges from reaching your small electronics. These surge protectors also include two 2.4-Amp USB ports to quickly charge USB-powered devices, including tablets.

Additional features of the MP1055WSS combo pack include EMI/RFI noise filters, metal oxide varistor (MOV) technology, surge protection LED indicators, impact-resistant casing and keyhole slots for easy mounting (strips only). All four surge suppressors come with a Limited Lifetime Warranty and a \$75,000 Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Consumer Electronics
- Personal Computers
- Chargers

FEATURES: POWER STRIPS

- Surge suppression: 1200 J
- USB ports: 2 (2.4-Amp)
- Plug type: NEMA 5-15P (45° off-set)
- Outlet type: 7 NEMA 5-15R
- Transformer outlets: 1
- Power cord: 4 ft.
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$75,000

FEATURES: WALL-TAPS

- Surge suppression: 1200 J
- Volts: 125 V
- Plug type: NEMA 5-15P
- Outlet type: 6 NEMA 5-15R
- USB charge ports: 2 (2.4-Amp)
- EMI/RFI Filtration: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$75,000

MP1055WSS

SURGE PROTECTOR MULTI-PACK SOLUTION

SPECIFICATIONS

	WALL-TAP	STRIP
INPUT		
Power Cord	Wall-Tap	4 ft. (1.2 m)
Plug Style	Wall-Tap	Right Angle - 45° Offset
OUTPUT		
Outlet Type	6 x NEMA 5-15R	7 x NEMA 5-15R
Outlets - Standard	6 x w/90° rotation	6 + 1 wide-spaced
USB Charge Ports	2 x 2.4 A (shared)	
USB Charge Ports Type	2 x Type A	
USB Charge Port Voltage	5 VDC	
SURGE PROTECTION AND FILTERING		
Surge Suppression (Joules)	1200 J	
Clamping Voltage	600V (L-G, L-N, N-G)	
EMI/RFI	Yes	
Maximum Surge Current	60,000 A	
Maximum Surge L-G	15,000 A (L-G)	
Maximum Surge L-N	30,000 A (L-N)	
Maximum Surge N-G	15,000 A (N-G)	
Response Time	<1 Nanosecond	
Attenuation	up to 32 dB	
Circuit Breaker	No	Yes
Surge Suppression (Joules)	1500 J	1200 J

	WALL-TAP	STRIP
LED INDICATORS		
Grounded/Protected	Yes	
PHYSICAL		
Physical Dimensions Width/Height/Depth (cm)	2.2 x 4.1 x 5.7 cm	2.74 x 2.19 x 12.2 cm
Shipping Dimensions Width/Height/Depth (cm)	36.51 x 40.64 x 6.99 cm	
Shipping Dimensions Width/Height/Depth (mm)	365.13 x 406.4 x 69.85 mm	
Shipping Dimensions Width/Height/Depth (in)	14.375 x 16 x 2.75 in.	
Shipping Weight (kg)	1.91 kg	
Shipping Weight (lbs.)	4.2 lbs.	
CERTIFICATIONS		
Environmental	RoHS Compliant	
Safety	UL1449 4th Edition	
WARRANTY		
CEG Amount	\$75,000	
Connected Equipment Guarantee	Lifetime	
Product Warranty	Limited Lifetime	