SONANCE

VISUAL EXPERIENCE DATA SHEET

VX46

TECHNICAL SPECIFICATIONS

VX46 SKU 96001 - Pair

Tweeter 0.75" (19mm) ceramic dome, Ferrofluid-

cooled, acoustic back chamber

Woofer 4.5" (114mm) Kevlar/Nomex cone,

rubber surround

Dispersion Technology Sinusoidal textured waveguide

Frequency Response 58Hz - 20kHz +/-3dB

Impedance 8 ohms nominal; 6 ohms minimum

Power Handling (RMS) 5 watts minimum; 80 watts maximum

Sensitivity (2.83V/1m) 90dB SPL

Mounting Technology Flex Frame 1 or 2-stage,

4 x RotoLock® Clamps

Micro Trim Grille (WxH) 5.47" x 8.8" (139.1mm x 223.6mm)

Trimless Grille (WxH) 5.13" x 8.46" (130.2mm x 214.8mm)

Speaker Mounting Depth (D) 3.28" (83.2mm)

Mounting Depth + Retrofit Encl. 3.84" (97.6mm)


Cut-Out Dims (WxH) 4.625" x 8" (117mm x 203mm)

Shipping Weight 6 lbs. (2.8kg)

DIMENSIONAL DRAWINGS



Cut-Out Width Front View



Mounting Depth (Open Back)

Side View



Mounting Depth + Retrofit Enclosure

Side View

VX 4" RECTANGLE ACCESSORIES

VX4-GRILLE-T

4" Micro Trim Rectangle Grille / Pair 93579

VX4-GRILLE-NT

4" Trimless Rectangle Grille / Pair 93580

VX4-ENCL

4" Rectangle Enclosure / Pair 96442

FLEXBRK-4

4" Rectangle Flex Bracket / 5xPair 92470

LIMITED LIFETIME WARRANTY