

# LINEAR HIGH BAY

## PRODUCT SELECTION GUIDE

		GOOD		BEST	
		tradeSELECT <sup>®</sup>		High-Spec Linear High Bay	
		 <b>CLB</b>		 <b>PEL</b>	
FEATURES	Length	2'	4'	2'	4'
		Mounting Height	Up to 60'		Up to 60'
	Lumens (maximum)	10,000- 57,000		8000–60,000	
	Efficacy (maximum LPW)	137–158		146–177	
	CRI	80		80+	
	CCT	4000K, 5000K		3000K, 3500K, 4000K, 5000K	
	Wattage	75–388W		50–410W	
	Voltage	120–277, 347–480*		120–277V, 347V, 480V	
	Distribution	Wide, Narrow*		Narrow, Wide, Lambertian	
	Lens	Polycarbonate		No Lens, Acrylic, Polycarbonate	
	Uplight	No		Yes	
	Temperature Range	-40° to 50° C		-40°C to 65°C	
	Dimming	0-10V Dimming to 10%		0–10V Dimming to 5%	
	Ratings	Damp Location, IP4X, IK10 Impact		Damp Location	
	Emergency Battery Pack	15W*		10W, 20W	
	Equivalency	100W to 1000W HID & 4–lamp T8, 8–lamp T5HO		100W to 1000W HID & 4–lamp T8, 8–lamp T5HO	
DLC <sup>®</sup> DesignLights Consortium	Yes		Yes		
Buy America(n) Solutions	–		TAA FAR §52.225-11		
INTEGRATED CONTROLS	Standalone Occupancy & Daylighting	Yes*		Yes	
	NX Standalone Occupancy & Daylighting	–		Yes	
	NX Networked Occupancy & Daylighting	–		Yes	
	PowerHUBB <sup>™</sup>	–		–	
USES	Applications	Industrial, Gymnasium, Warehouse, Big Box Retail		Industrial, Gymnasium, Warehouse, Big Box Retail	

DLC<sup>®</sup> (DesignLights Consortium) Qualified. Please refer to the DLC website for specific product qualifications at [www.designlights.org](http://www.designlights.org)