



JP-100G-LH

2 Piece, Full Port, Press Connection with Leak Detection, Locking Handle, 250 WOG

PART NUMBER	SIZE
100-203G-LH	1/2"
100-204G-LH	3/4"
100-205G-LH	1"
100-206G-LH	1-1/4"
100-207G-LH	1-1/2"
100-208G-LH	2"

- Dezincification Resistant Brass Alloy
- Triple Sealing Stem with 2 FKM O-Rings and 2nd Generation PTFE Seal
- Press Connection with Leak Detection O-Rings
- Blow-Out Proof Stem
- 100% Leak Tested
- 100% Made in Italy
- NSF 61 & NSF 372 Certified
- Leakproof Stem - Lifetime Warranty
- 20 in-Hg Vacuum Rating
- Wetted Surfaces Contain Less than .25% Lead Content



JP-100G-IH

2 Piece, Full Port, Press Connection with Leak Detection, Insulated Handle, 250 WOG

PART NUMBER	SIZE
100-203G-IH	1/2"
100-204G-IH	3/4"
100-205G-IH	1"
100-206G-IH	1-1/4"
100-207G-IH	1-1/2"
100-208G-IH	2"

- Dezincification Resistant Brass Alloy
- Triple Sealing Stem with 2 FKM O-Rings and 2nd Generation PTFE Seal
- Press Connection with Leak Detection O-Rings
- Blow-Out Proof Stem
- 100% Leak Tested
- 100% Made in Italy
- UL 2043 Certified handle
- NSF 61 & NSF 372 Certified
- Leakproof Stem - Lifetime Warranty
- Wetted Surfaces Contain Less than .25% Lead Content



JP-100G XLC

2 Piece, Full Port, Press XLC Connection, 250 WOG

PART NUMBER	SIZE	CASE	WEIGHT
100-209XLCG	2-1/2"	2	18
100-210XLCG	3"	2	28
100-211XLCG	4"	1	26

- Dezincification Resistant Brass Alloy
- Triple Sealing Stem with 2 FKM O-Rings and 2nd Generation PTFE Seal
- Blow-Out Proof Stem
- 100% Leak Tested
- 100% Made in Italy
- Leakproof Stem - Lifetime Warranty
- Wetted Surfaces Contain Less than .25% Lead Content

