# Power Supply Replacement Cords

3-Conductor Grounded • Types SJ, SJOW and SJOOW • 60˚C • 300 Volts

| CATALOG NUMBER | CORD TYPE | NO. OF COND. | AWG SIZE | LENGTH OF CORD (FT) | COLOR OF JACKET | POWER RATING | | | NEMA CONFIG. | PLUG CONFIG. | PKG. PER CTN. | WT./ UNIT LBS | WT./ CTN. LBS | UPC CODE |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | VOLTS | AMPS | WATTS | | | | | | |
| 02685.70.01 | SJOOW | 3 | 18 | 8 | Black | 125 | 10 | 1250 | 5-15P | Straight | 25 | 0.6 | 14 | 079407026852 |
| 02686.70.01 | SJOW | 3 | 16 | 8 | Black | 125 | 13 | 1625 | 5-15P | Straight | 35 | 0.7 | 24 | 079407026869 |
| 04932.70.01 | SJ | 3 | 16 | 12 | Black | 125 | 13 | 1625 | 5-15P | Straight | 50 | 0.8 | 40 | 079407049325 |
| 04929.70.01 | SJ | 3 | 16 | 9 | Black | 125 | 13 | 1625 | 5-15P | Straight | 50 | 0.6 | 30 | 079407049295 |
| 04926.70.01 | SJ | 3 | 16 | 6 | Black | 125 | 13 | 1625 | 5-15P | Straight | 50 | 0.6 | 28 | 079407049264 |



**Product Construction:**

**Conductor:**
- 18 AWG or 16 AWG stranded bare copper per ASTM B174

**Insulation:**
- Premium-grade, color-coded EPDM

**Jacket:**
- CPE; black

**Applications:**
- For replacement use

**Features:**
- For replacement use
- Straight plug

**Industry Approvals:**
- UL Listed
- CSA

# Power Supply Replacement Cords

2 and 3 Conductor • Types SJT and ST • 60˚C • 300 Volts and 600 Volts

| CATALOG NUMBER | CORD TYPE | NO. OF COND. | AWG SIZE | LENGTH OF CORD (FT) | COLOR OF JACKET | POWER RATING | | | NEMA CONFIG. | PLUG CONFIG. | PKG. PER CTN. | WT./ UNIT LBS | WT./ CTN. LBS | UPC CODE |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | VOLTS | AMPS | WATTS | | | | | | |
| **300 Volt** | | | | | | | | | | | | | | |
| 02523.73.01 | SJT | 3 | 18 | 3 | Black | 125 | 10 | 1250 | 5-15P | Straight | 50 | 0.2 | 12 | 079407025237 |
| 01364.70.01 | SJT | 3 | 18 | 8'2" | Black | 125 | 10 | 1250 | 5-15P | Straight | 50 | 0.5 | 25 | 079407213641 |
| 02052.70.01 | SJT | 3 | 18 | 12 | Black | 125 | 10 | 1250 | 5-15P | Straight | 50 | 0.7 | 36 | 079407020522 |
| 02524.73.01 | SJT | 3 | 16 | 3 | Black | 125 | 13 | 1625 | 5-15P | Straight | 50 | 0.3 | 14 | 079407025244 |
| 02547.70.01 | SJT | 3 | 16 | 6 | Black | 125 | 13 | 1625 | 5-15P | Straight | 25 | 0.5 | 13 | 079407018444 |
| 01513.70.01 | SJT | 3 | 16 | 8'2" | Black | 125 | 13 | 1625 | 5-15P | Straight | 45 | 0.7 | 32 | 079407315130 |
| 04949.60.10 | SJT | 3 | 16 | 9 | Gray | 125 | 13 | 1625 | 5-15P | Straight | 50 | 0.7 | 35 | 079407049493 |
| 01614.70.01 | SJT | 3 | 16 | 12 | Black | 125 | 13 | 1625 | 5-15P | Straight | 50 | 0.9 | 44 | 079407016143 |
| 01278.70.01 | SJT | 2 | 16 | 8 | Black | 125 | 13 | 1625 | 1-15P | Straight | 30 | 0.5 | 14 | 079407012787 |
| 01950.70.01 | SJT | 3 | 14 | 8 | Black | 125 | 15 | 1875 | 5-15P | Straight | 50 | 0.8 | 41 | 079407019502 |
| **600 Volt** | | | | | | | | | | | | | | |
| 01951.70.01 | ST | 3 | 12 | 8 | Black | 125 | 15 | 1875 | 5-15P | Straight | 25 | 1.8 | 45 | 079407719518 |



| With Switch | CORD TYPE | NO. OF COND. | AWG SIZE | LENGTH OF CORD (FT) | COLOR OF JACKET | POWER RATING | | | NEMA CONFIG. | PLUG CONFIG. | SWITCH SPEED | PKG. PER CTN. | WT./UNIT LBS | WT./CTN. LBS | UPC CODE |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | VOLTS | AMPS | WATTS | | | | | | | |
| 01732.70.01 | SJT | 3 | 18 | 8 | Black | 125 | 10 | 1250 | 5-15P | Straight | 1 Speed (On/Off) | 25 | 0.7 | 18 | 079407017324 |
| 02053.70.01 | SJT | 3 | 18 | 12 | Black | 125 | 10 | 1250 | 5-15P | Straight | 1 Speed (On/Off) | 15 | 0.8 | 12 | 079407020539 |

| With Strain Relief | CORD TYPE | NO. OF COND. | AWG SIZE | LENGTH OF CORD (FT) | COLOR OF JACKET | POWER RATING | | | NEMA CONFIG. | PLUG CONFIG. | STRAIN RELIEF | PKG. PER CTN. | WT./UNIT LBS | WT./CTN. LBS | UPC CODE |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | VOLTS | AMPS | WATTS | | | | | | | |
| 02548.70.01 | SJT | 3 | 16 | 6 | Black | 125 | 13 | 1625 | 5-15P | Straight | 7" From Free End | 25 | 0.5 | 13 | 079407025480 |

| With Receptacle Only | CORD TYPE | NO. OF COND. | AWG SIZE | LENGTH OF CORD (FT) | COLOR OF JACKET | POWER RATING | | | NEMA CONFIG. | RECEPTACLE CONFIG. | PKG. PER CTN. | WT./UNIT LBS | WT./CTN. LBS | UPC CODE |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | VOLTS | AMPS | WATTS | | | | | | |
| 04530.73.01 | SJT | 3 | 16 | 3 | Black | 125 | 13 | 1625 | 5-15R | Straight | 50 | 0.2 | 9 | 079407045303 |

**Product Construction:**

**Conductor:**
- 18 AWG through 12 AWG stranded bare copper per ASTM B174

**Insulation:**
- Premium-grade, color-coded PVC

**Jacket:**
- PVC; black or gray

**Applications:**
- For replacement use

**Features:**
- Straight plug
- Conductor stripped 5/8"
- Jacket removed 1 1/2"

**Industry Approvals:**
- UL Listed
- CSA

CAROL BRAND

UL LISTED

Certified Canadian Standard Association

General Cable