

CL3R/CMR Non-shielded 300V 12 AWG & 14 AWG

CL3R - Nonshielded Conductors
PVC Insulation & Jacket
300 Volt - 14 AWG & 12 AWG

Security and Alarm Cable

Image Coming Soon

Category Conductor Description:

- Stranded bare copper to ASTM B-3, B-8, and B-286

Category Insulation Description:

- Color coded Polyvinyl Chloride (PVC)

Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC)
Includes ripcord

Applications:

- Power limited control circuits
- Wiring of the following systems: Intercom, Security, Audio
- Suggested Voltage Rating: 300 Volts

Standards:

- NEC Article 725 Type CL3R
- CSA CMG 60C FT-4

PART NUMBER TABLE

Part#	Gauge	Conductors	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')	Material Weight (KG/KM)
DS91402	14	2	0.013	0.015	0.224	38	56
DS91403	14	3	0.013	0.015	0.239	54	80
DS91404	14	4	0.013	0.015	0.264	65	96
DS91202	12	2	0.014	0.02	0.26	54.9	81

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •
Seattle • St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC