

60-Watt Equivalent A19 LED Smart Wi-Fi Bulbs (3-Pack)



- Works with Amazon Alexa and Google Assistant for voice control
- Turn on/off and adjust lighting with your smartphone
- Intuitive mobile app eliminates the need for any smart home hubs

Product Specifications

Item Number: **BPA800/RGBW/AG/3/UK**

Lighting technology used	LED
Non-directional or directional	Non-Directional
Light source cap-type (or other electric interface)	B22
Correction factor C depending on light source characteristics-Main or non-mains	Non-Main
Connected light source (CLS):	
Useful luminous flux(Lm)*	800
Correlated colour temperature (K) *	2700K-6500K
Chromaticity coordinate (x):	
Chromaticity coordinate (y):	
The beam angle or range of beam angles(0)*	N/A
Beam angle correspondence : Sphere or wide cone or narrow cone	
Electrical interface details*	220-240 Vac; 50Hz; B22
The L70B50 life time expressed in hours	25,000
The on-mode power (Pon) expressed in W	9.0
Lamp Dimensions(mm)	106*60
The standby power (Psb) expressed in W	N/A
The networked standby power (Pnet) for CLS expressed in W	0.43
The Colour rendering index 80	80
Survival factor (Max value =1)	1
Lumen maintenance factor (Max value =1)	96.70%
Displacement factor (Max value =1)	0.956
Colour consistency in McAdam ellipses (Max value =9)	2.6
Flicker metric (Max value =9.9)	0.003
Stroboscopic effect metric (Max value =9.9)	0.004
Spectral power distribution in the range 250 nm to 800 nm, at full-load (File to be uploaded)	
If the light source is designed for optimum use in nonstandard conditions (such as ambient temperature Ta ≠ 25 0C or specific thermal management is necessary)	N/A
A warning if the light source cannot be dimmed or can be dimmed only with specific dimmers or with specific wired or wireless dimming methods	Dimmable
Mercury content x,x mg (if applition) 0,0	0
Energy consumption in on-mode (KWh/1000h):	
Energy Efficacy Class	F