



Lubricants


## ADHESIVE LUBRICANT

### MULTI-PURPOSE ADHESIVE LUBRICANT

Adhesive Lubricant is a multi-purpose lubricant with a temporary blue tint to assist with application coverage. It exhibits strong attachment to substrates, is non-dripping, has good penetrating properties, is resistant to high pressure and has excellent water repellence.

Blue Adhesive Lubricant produces a very low coefficient of friction and reduces stick slip problems. It provides long lasting lubrication and it is functional over a wide temperature range.

### PRODUCT CODES / FILL SIZES

 1031491  
32500 / 400ml

### APPLICATIONS

- Engine assembly
- Handling equipment
- Chains
- Bearings
- Railroad equipment
- Agricultural equipment
- Surface treatment
- Guide rails
- Hinges
- Cables

### DIRECTIONS

- Apply to a clean, dry surface
- Apply a thin even film
- Allow a few minutes for good penetration
- Do not use on energised equipment
- Do not mix with other lubricants
- To remove residues or excess product, use a solvent based Ambersil cleaner



#### CRC INDUSTRIES UK LTD

Wylds Road, Bridgwater  
Somerset, TA6 4DD  
United Kingdom

t +44 (0)1278 727200  
e sales.uk@crcind.com  
w www.ambersil.com

Version 4.2  
Created: July 2019  
Updated: October 2024

# TECHNICAL DATA

## TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Blue viscous liquid
Odour	Solvent
Density	0.80 g/cm <sup>3</sup> (@20°C)
Flash Point	< 0°C
Density Active Product	0.87 (@25°C)
Flash Point Active Product	230°C (Open Cup)
Dynamic Viscosity Active Product	1894 mPa.s (@40°C)
4-ball Wear	0.25mm <sup>2</sup>
Operating Temperature	-12°C to +150°C (180°C intermittent)

## MATERIALS COMPATIBILITY

OK	Safe on all metal surfaces (does not stain), most rubbers, plastics and coatings. Test on sensitive or stressed materials before use.
CAUTION	-
NOT OK	-

## STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

## HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via [info.uk@crcind.com](mailto:info.uk@crcind.com)

## MISREPRESENTATION ACT 1967

## TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.



### CRC INDUSTRIES UK LTD

Wylde Road, Bridgwater  
 Somerset, TA6 4DD  
 United Kingdom  
 t +44 (0)1278 727200  
 e [sales.uk@crcind.com](mailto:sales.uk@crcind.com)  
 w [www.ambersil.com](http://www.ambersil.com)  
 Page 2 / 2  
 Version 4.0  
 Created: July 2019  
 Updated: October 2024  
 Company Registered No. 04910479 VAT No. GB 821 5195 42

**YOUR  
COMPLETE  
MAINTENANCE  
SOLUTION™**