Moonstruck

Porcelain Stone®

Colors



AV301 ▶ Juno UPS



AV301 ▶ Juno HON



AV304 ▶ Gemini UPS



AV304 ▶ Gemini HON



AV302 ▶ Luna UPS



AV302 ▶ Luna HON



AV305 ▶ Apollo UPS



AV305 ▶ Apollo HON



AV303 ▶ Kosmos UPS



AV303 ▶ Kosmos HON

Features and Benefits

- Visually replicated from the moons of our solar system in five striking shades
- Sizes offered 12 x 24 and 18 x 36 rectified tile in both unpolished and honed finishes
- Trim includes 4 x 24 single bullnose
- Contains a minimum of 4% pre-consumer recycled content and is manufactured by Crossville® using processes that is Green SquaredSM certified
- · Cross-Sheen® finish for easy cleaning
- Plank shapes are also available through Crossville's Get Planked® program, which offers a variety of plank sizes with no minimum order and a short lead time



Moonstruck Porcelain Stone®

Sizes (Available in all colors)







AV305 ▶ Apollo 12 x 24 HON

Sizes & Finishes

4	Field Tile			
	Nominal (in)	Actual (mm)	Thickness (mm)	Finish
	12 x 24	297 x 597	10.5	UPS/HON
	18 x 36	447 x 897	10.5	UPS/HON

Crossville recommends a grout joint of 3mm

Actual measurements stated in inches indicate tile is calibrated (non-rectified

Coordinating Trim

Nominal (in)	Actual (mm)	Thickness (mm)	Finish
4 x 24 Single Bullnose	96 x 597	10.5	UPS/HON

4 x 24 Single Bullnose

Product Performance

Breaking Strength	>500 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.20%	ASTM C373
Scratch Hardness	7	Mohs Scale

Wet Dynamic Coefficient of Friction Range

UPS	0.50 - 0.60	AcuTestsm
HON	0.42 - 0.52	AcuTestsm

Shade & Texture Index

Moonstruck has a shade variation of V3.



V1 Uniform appearance

V3 Moderate Variation

This porcelain tile product is produced with a V3 variation. Expect that the amount of color and texture on each piece may vary significantly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation

Get Planked!

Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick fulfillment.

See website for more details and sizes.





Moonstruck

Crossville, Inc.

PO Box 1168 Crossville, TN 38557

Phone 931.484.2110 931.456.2956 Fax

E-Mail Crossc@CrossvilleInc.com

Web CrossvilleInc.com

Recommended Use

Moonstruck is recommended for interior floors, walls, countertops, and exterior walls in both residential and commercial applications. Moonstruck is not recommended for exterior horizontal surfaces or exterior paving. The honed finish is not recommended for wet areas where standing water may occur. If offset pattern is required for tiles 18 inches or longer, Crossville® recommends an offset of not greater than 33%. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage. See CrossvilleInc.com for detailed installation instructions.

Care and Maintenance

Regular cleaning is the best way to keep Moonstruck tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More Information regarding the care and maintenance of Crossville® products is available at CrossvilleInc.com.



EcoCycle Tile Process™

Moonstruck contains a minimum of 4 percent pre-consumer recycled content and is manufactured by Crossville® using processes that recycle nearly 12 million pounds of previously discarded filtrate and fired tile waste. In addition to its own fired waste recycling, Crossville also accepts and recycles reclaimed, previously installed tile through its Tile Take-Back™ Program. For more information, visit CrossvilleInc.com/

Green SquaredSM Certified

Crossville® has earned Green SquaredSM certification from the Tile Council of North America (TCNA) for its entire U.S.-manufactured porcelain product line-up, as well as its manufacturing processes. The company is among the first ever recipients of this certification standard for the tile industry. TCNA developed the Green Squared certification under American National Standards Institute (ANSI) process. The multi-attribute program (ANSI A138.1) scores products in five categories of performance: product characteristics, manufacturing, corporate governance, innovation and end-of-life. Crossville's certified products and processes received stringent evaluation from Scientific Certification Systems (SCS), the green building industry's longest standing third-party certifier.

Our porcelain tiles are available with Hydrotect™. Crossville's revolutionary invisible coating harnesses the power of light, water, and oxygen to create the best defense against dirt and pollution. Whether indoors or out, floors and walls stay cleaner, providing a superior experience in any space. For complete details check our website at CrossvilleInc.com.

♠ HYDROTECT*

by **CROSSVILLE**.

AV304 ▶ Gemini 18 x 36 UPS and HON

Environmentally Aware

National Accounts

For over 20 years we have been offering Porcelain tile to commercial customers at National Accounts pricing programs with special discounts. The National Accounts department provides materials forecasting, sales support and samples.

Exterior Cladding

Crossville's Porcelain Stone® Exterior Cladding Systems are suitable for virtually any conventional masonry application. When used in conjunction with our exterior cladding systems, Crossville's Porcelain Stone offers clear advantages: decreased construction costs, less site disturbance, low-tozero maintenance after installation, accelerated construction schedules and greater strength than traditional masonry.

Crossville® Sample Express

Sample fulfillment & Help Line Samples@CrossvilleInc.com 1800221.9093

Loose Samples for Architects & Designers

Loose Tile Samples

Sizes may vary depending on product series Max. of 4 large field tile per order

Replacement Chips for PSS Rack Max. of 5, 2 x 2 chips per color

Standard Shipping **UPS** Ground

Our Warranty

Crossville Inc. guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1-2012 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com.

Information listed here is subject to change. Please refer to CrossvilleInc.com for the latest, most accurate information.

Trade Organizations



















