

# Straight Blade Devices

## Accessories

For 3 Wire 30 and 50 Ampere, 125 and 250 Volts and 277 Volts AC



### Wallplates

Description	Color	Single Receptacle Plate 2.16 in. (54.9) Dia.
Thermoplastic, smooth, 1-gang.	Black	<b>P724BK</b>
Thermoplastic, smooth, 2-gang.	Black	<b>P703BK</b>
Aluminum, .05 in. (1.3), 1-gang, smooth horizontal brushed finish.		<b>SA723</b>
Stainless steel 302/304, .035 in. (0.9), 1-gang, smooth horizontal brushed finish.		<b>SS723</b>
Stainless steel 302/304, .035 in. (0.9), 2-gang, smooth horizontal brushed finish.		<b>SS703</b>



**P724BK**

**SS723**



**SS703**



**IP44**  
SUITABILITY

### Weatherproof Lift Covers

Description	Catalog Number
Cast aluminum for FS/FD box mounting for 30A.	<b>HBL9420</b>
Cast aluminum for FS/FD box mounting for 50A.	<b>HBL9425</b>



**HBL9420**

### PLUGOUT® Device

Description	Catalog Number
Electrical plug lockout device for 30, 50 and 60A devices.	<b>HLD2</b>

Note: See section BB for additional information on lockout devices.



**HLD2**

Dimensions in Inches (mm)