



DEHUMIDIFIER

FLAT PANEL | 22-PINT | 35-PINT | 50-PINT



3PFD22
4PFD35



4PFD50



**3-WAY
DRAINAGE**
BUCKET | PUMP | GRAVITY

	3PFD22	4PFD35	4PFD50	4PFD50
UPC	842149000486	842149003210	842149003227	842149003234
CAPACITY (pts./day)	22	35	50	50
COVERAGE (sq. ft.)	1,500	3,000	4,500	4,500
PUMP	—	—	—	✓
EEV	1.7	2.01	2.01	2.01
FAN SPEEDS	2	2	2	2
AMPS	2.2	3.5	4.6	4.6
WATTS	250	360	470	470
DECIBELS (Hi/Low)	52/46.5	52/48.5	51/49	51/49
BUCKET CAPACITY (pts.)	6.3	10.6	12.7	12.7
UNIT DIMENSIONS (WxHxD) (in.)	15.5 × 19.75 × 10.25	15.5 × 19.75 × 10.25	15.5 × 24.25 × 11	15.5 × 24.25 × 11
PKG. DIMENSIONS (WxHxD) (in.)	16.5 × 20.5 × 11.5	16.5 × 20.5 × 11.5	17 × 26 × 13	17 × 26 × 13
CONTAINER QTY (20'/40'/40' HQ)	432/880/1100	432/880/1100	288/582/775	288/582/775
WEIGHT (Net/Gross) (lbs.)	32.5/34.5	34.5/36.5	41.25/44.5	42.25/45.25
MIN. OPERATING TEMP	41°F	41°F	41°F	41°F
REFRIGERANT	R32	R32	R32	R32
OUTLET CONFIGURATION	 15A - 115V	 15A - 115V	 15A - 115V	 15A - 115V

FEATURES

- Continuous drainage
- Adjustable digital humidistat provides precise humidity control
- Automatic defrost prevents evaporator from freezing
- Automatic shut off when bucket is full
- Comfort mode controls humidity based on room temperature
- Soft-touch electronic control panel
- Low temperature operation (down to 41°F)
- 24-hour programmable timer
- Ultra-quiet operation
- Easy roll casters
- Bucket full indicator
- Reusable filter
- Pump function ejects water to a sink or window, up to 16 vertical feet - perfect for areas where a floor drain is unavailable. (3PFD50)

