SONANCE

VISUAL EXPERIENCE DATA SHEET

VX86R

TECHNICAL SPECIFICATIONS

VX86R

SKU 96017 - Pair

Tweeter 1.2" (30mm) ceramic dome, Ferrofluid-cooled,

acoustic back chamber

Woofer 8" (203mm) Kevlar/Nomex cone,

rubber surround, pivoting

Dispersion Technology Sinusoidal textured waveguide

Speaker Pivot Coincident woofer and tweeter, +/-13° pivot

Frequency Response 34Hz - 20kHz +/-3dB

Impedance 8 ohms nominal; 6 ohms minimum

Power Handling (RMS) 5 watts minimum; 150 watts maximum

Sensitivity (2.83V/1m) 91dB SPL

Mounting Technology Flex Frame 1 or 2-stage, 4 x RotoLock® Clamps


Round Micro Trim Grille (Dia) 11.52" (292.6mm)
Round Trimless Grille (Dia) 11.17" (283.8mm)

 Square Micro Trim Grill (WxH)
 11.52" x 11.52" (292.6mm x 292.6mm)

 Square Trimless Grille (WxH)
 11.17" x 11.17" (283.8mm x 283.8mm)

Speaker Mounting Depth (D)5.51" (140mm)Mounting Depth + Retrofit Encl.6.52" (165.6mm)Cut-Out Dims (Dia)10.125" (257mm)Shipping Weight20.0 lbs. (9.0kg)

DIMENSIONAL DRAWINGS



Cut-Out Diameter Front View



Mounting Depth (Open Back)

Side View



Mounting Depth + Retrofit Enclosure

Side View

VX 8" ROUND ACCESSORIES

VX8R-GRILLE-T 8" Micro Trim Round Grille / Pair	93577
VX8R-GRILLE-NT 8" Trimless Round Grille / Pair VX8SQ-T	93578
8" Micro Trim Square Adapter / Pair VX8SQ-T-5PR	96031
8" Micro Trim Square Adapter / 5xPair VX8SQ-NT	96034
8" Trimless Square Adapter / Pair VX8SQ-NT-5PR	93587
8" Trimless Square Adapter / 5xPair VX8-ENCL-R	93590
8" Round Enclosure / Pair FLEXBRK-8-R	96243
8" Round Flex Bracket / 5x Pair	92247

LIMITED LIFETIME WARRANTY