














## Plates for Use in SystemOne 2, 4 and 6-Gang Floor Boxes

- UL 514A listed

Plate Style	(1) Decorator Opening	(1) Duplex Opening	(2) Extron® MAAP Openings	(2) Extron® Openings
Cat. No.	<b>FBMPREC</b>	<b>FBMPDUP</b>	<b>FBMPMAAP</b>	<b>FBMPAAP</b>
				
Plate Style	(2) 1U Hubbell iStation Openings	(1) 1.5U Hubbell iStation Opening	(1) Simplex Opening 1.40 in. Diameter	(1) Twist-Lock® Opening 1.60 in. Diameter
Cat. No.	<b>FBMP2IM</b>	<b>FBMP15IM</b>	<b>FBMP139</b>	<b>FBMP156</b>
				
Plate Style	1-Gang Blank	Cable Feed Through with Bushing	(1) Opening for TracJack® or Series II®	(1) Opening with Hubbell ISF6 Frame for Keystone Jacks
Cat. No.	<b>FBMPBNK</b>	<b>FBMPFT</b>	<b>FBMPTRAC</b>	<b>FBMP6KS</b>
				
Plate Style	(2) Hubbell Jack Openings and (4) Jack KOs with Label Field			
Cat. No.	<b>FBMP6DJ</b>			
				

## Pre-Wired Device Plates

- Reduces wiring and installation times
- 8 in. stranded leads mounted to the face plate

Description	Type	15A	20A
Duplex, Gray.	Standard Tamper-Resistant	<b>PWFBMPCR15GRY</b> <b>PWFBMPCR15GRYTR</b>	<b>PWFBMPCR20GRY</b> <b>PWFBMPCR20GRYTR</b>
Decorator, Gray.	Standard Tamper-Resistant	<b>PWFBMPCR15GRY</b> <b>PWFBMPCR15GRYTR</b>	<b>PWFBMPCR20GRY</b> <b>PWFBMPCR20GRYTR</b>



## Accessories

Description	Standard Epoxy Coating	Catalog Number
2 in. threaded zinc hub for use with <b>CFB2G30</b> , <b>CFB4G30</b> and <b>CFB6G30</b> series floor boxes; replaces <b>CFBKOPLATE</b> .		<b>CFBHUB2</b>
Replacement knock-out plate.		<b>CFBKOPLATE</b> <b>CFBKOPLATECR</b>
CFB4G series replacement dividers.		<b>CFB4GDIVKIT</b>
CFB6G series replacement dividers.		<b>CFB6GDIVKIT</b>
Stackable ring to increase box height and concrete pour depth by ¼ in. increments above top plane of floor box. One ring per ¼ in. depth increase.	2-Gang	4 and 6-Gang
<b>Must be installed before concrete pour.</b>	<b>CFB6RCVRR075</b>	<b>CFB8RCVRR075</b>
Finished floor height adjustment ring - <b>increase post pour adjustment</b> ; use with round cover series.	0 - ¼ in. ¼ in. - ½ in. ½ in. - ¾ in.	<b>CFB6RCVRR1**</b> <b>CFB6RCVRR2</b> <b>CFB6RCVRR3</b>
2 and 4-gang rectangular pre-pour ½ in. extension caps (2 pack).		<b>24GEXTENDCAP2PK</b>
6 and 10-gang rectangular pre-pour ½ in. extension caps (2 pack).		<b>610GEXTENDCAP2PK</b>

Note: \*Included with standard **CFB2G30R** and **CFB2G25R** series.  
\*\*Included with standard **CFB4G30R** and **CFB4G25R** series.

Extron® is a registered trademark of Extron Electronics.  
Crestron® is a registered trademark of Crestron Electronics, Inc.  
FSR® is a registered trademark of FSR Inc.  
TracJack®, Series II® and Ortronics® are registered trademarks of Ortronics/Legrand.



Dimensions in Inches (mm)