

AP8841

APC Rack PDU, 2G, metered, 0U, 30A, 200V and 208V, 36 C13 and 6 C19 sockets



Overview

Presentation

APC Metered Rack PDUs distribute reliable rack power distribution via a single input with multiple output receptacles. Real-time remote monitoring and user-defined alarms help prevent potential circuit overloads that can cause accidental power loss to critical equipment. Easily access, configure, and manage this metered PDU from remote locations. A network management interface provides standards-based management via Web, SNMP, and Command Line Interface. This Metered PDU from APC provides (36) IEC 60320 C13 and (6) IEC 60320 C19 outlets to supply power to rack equipment. Locking IEC receptacles enable locking power cord compatibility to reduce the probability of accidentally disconnecting cords and dropping loads. Volts, amps, real power (kW), and energy (kWh) data is provided to support energy management. An embedded log memory to reports historic metered data. Display details current, power, and voltage measurements and offers local user access. An environmental monitoring port for external temperature/humidity monitoring is available (sensor sold separately model AP9335T or AP9335TH). Easily mount this vertical PDU in racks or enclosures. It occupies zero U of valuable rack space, which allows space for more equipment in the rack. This vertical PDU does not require additional tools to mount into APC NetShelter Enclosures. Enables a quick recovery from overload events and breakers are ultra-low profile. Packaging Includes PDU, Installation guide, Rack Mounting brackets, Safety guide, Serial configuration cable.

Lead time

Usually in Stock

Main

Color	Black
Product or Component Type	PDU
PDU Type	Metered
Cord length	9.84 ft (3.00 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets Serial configuration cable Safety guide

Complementary

Input Voltage	200 V 208 V
Height	70.51 in (179.1 cm)
Width	2.20 in (5.6 cm)
Output Voltage	200 V 208 V
Depth	1.73 in (4.4 cm)
Net Weight	15.08 lb(US) (6.84 kg)
Mounting Location	Side
Mounting preference	No preference

Input Plug Type	NEMA L6-30P
Mounting Mode	Rack-mounted
Rack units	0U
USB compatible	No
Mounting position	Vertical
Line Rated Current	24 A
Acceptable Input Voltage	200...240 V
Input current limits	30 A
Load Capacity	4992 VA
Input Frequency	50/60 Hz
Outlet type and quantity	36 IEC 60320 C13 6 IEC 60320 C19

Environment

Product Certifications	METI Denan[RETURN]PSE[RETURN]VDE
Standards	CSA C22.2 No. 60950 IEC 60950 UL 60950-1
Ambient air temperature for operation	23...140 °F (-5...60 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	731304277002
Returnability	No
Country of origin	IN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	78.74 in (200 cm)
Package 1 Width	4.21 in (10.7 cm)
Package 1 Length	6.38 in (16.2 cm)
Package 1 Weight	18.67 lb(US) (8.47 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------