

# WAVY GLASS WALL TILE



PEARL C101



CLOUD CREAM C104



VINTAGE MINT C107



MINK C119



SILVER CLOUD C102



PLAZA TAUPE C105



FOUNTAIN BLUE C108



CHARCOAL GRAY C121

## SIZES

		THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
4 x 12 Wavy Wall Tile	3-7/8" x 11-3/4" (9.80 cm x 29.80 cm)	5/16"	6.66	20

#### **INSTALLATION & PRICING**

RECOMMENDED GROUT JOINT: Wall: 1/8"
RELATIVE PRICING: High

SHADE VARIATION



#### PERFORMANCE CHARACTERISTICS

	ASTM#	WALL RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	>100 lbs.
Scratch Hardness	MOHS	4.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: americanolean.com/information/TestResults.

## USAGE

FLOORS	WALLS	COUNTERTOPS
P	W	<b>Ø</b>

## **APPLICATIONS**

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	•
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of  $\geq$ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest  $^{\text{TM}}$ , visit americanolean.com/DCOF.

#### APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

# **NOTES**

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

Since there are variations in all glass products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.2 standards.

Use of a white latex modified thin-set is recommended for installation.