

SL-RL7ND

6 TON INLINE COMPRESSION TOOL—WITH CHANGEABLE HEADS



NEW

SL-RL7ND

SERIES 7R
PRO LINE

FEATURES

Ergonomic design for easy one-hand operation

180° rotating head with forged jaws and protective brush guards

Pull-pin head design allows quick change of available jaws

Accepts all "W", "X" & "O" type dies depending on jaw selected

5 yr. Tool/3 yr. Battery—Huskie Tools Limited Warranty

CUTTING CAPACITIES

	EVS-ACSRJAW	EVS-CUALJAW	SLGW-JAW
COPPER	Up to 350 MCM	Up to 750 MCM	Up to 4/0
ALUMINUM	Up to 350 MCM	Up to 1" O.D.	Up to 4/0
ACSR	Up to 556 MCM	<i>Do Not Cut</i>	Up to 4/0
EHS GUY WIRE, SOFT LOCKS, SOFT STEEL BOLTS	<i>Do Not Cut</i>	<i>Do Not Cut</i>	Up to 3/8" Dia.

CONNECTOR RANGE

LUGS & SPLICES	#8 to 500 MCM Cu #8 to 350 MCM Al
H-TAPS	Up to 4/0-4/0

SPECIFICATIONS

CRIMP FORCE	6 Ton
WEIGHT	5.9 lbs (2.7 kg)
DIMENSIONS (H X L X W)	15.80" x 4.50" x 3.30", 401 x 115 x 84 mm

PRODUCT NO.	JAW	BATTERY (QTY)	CHARGER	TOOL BAG
SL-RL7ND	ND JAW 	(2) MILWAUKEE REDLITHIUM™ 5.0Ahr	120VAC	Included
SL-RL7NDDC		(2) MILWAUKEE REDLITHIUM™ 5.0Ahr	12VDC	
SL-RL7NDX		Not Included	N/A	
SL-RL7NDBG	BG JAW 	(2) MILWAUKEE REDLITHIUM™ 5.0Ahr	120VAC	Included
SL-RL7NDBGDC		(2) MILWAUKEE REDLITHIUM™ 5.0Ahr	12VDC	
SL-RL7NDBGX		Not Included	N/A	
SL-RL7NDO	O JAW 	(2) MILWAUKEE REDLITHIUM™ 5.0Ahr	120VAC	Included
SL-RL7NDODC		(2) MILWAUKEE REDLITHIUM™ 5.0Ahr	12VDC	
SL-RL7NDOX		Not Included	N/A	
SL-RL7NDK	K JAW 	(2) MILWAUKEE REDLITHIUM™ 5.0Ahr	120VAC	Included
SL-RL7NDKDC		(2) MILWAUKEE REDLITHIUM™ 5.0Ahr	12VDC	
SL-RL7NDKX		Not Included	N/A	

Huskie Tools is not affiliated with, authorized, or endorsed by Milwaukee Electric Tool Corporation. Milwaukee listed batteries and chargers are being re-sold by Huskie Tools. Milwaukee® M18™ REDLITHIUM™ are registered trademarks of Milwaukee Electric Tool Corporation. Huskie Tools is not affiliated with, authorized, or endorsed by Makita® Corporation. Makita® listed batteries and chargers are being re-sold by Huskie Tools. Makita® and LXT® are registered trademarks of Makita® Corporation.