



Structured Cable Products

Quality Installations Deserve Quality Products

SPECIFICATION SHEET

Phone: 866-470-5742
www.scpcat5e.com

30-May-2014

Product Number : **14/4-GY**

RoHS

**Unsh Riser 4/C 14/19 AWG SBC
PVC Insulation
Gray PVC Riser Jacket
1000 FEET Plywood Spool**

Conductor :	14 AWG 19 Strand SBC Cond.		
Total Cable Weight :	105 kg/km	Final Diameter :	0.267 inches
Insulation :	PVC	Jacket :	PVC
DC Resistance 25°C :	2.7 Ohms / 1000 ft	Mutual Capacitance :	22.3 pF /ft
Impedance :	74.8 Ohms		
Velocity of Prop :	70 %	Inductance. :	1.2 mH /km

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS --- P/N 14/4 --- (UL) CL3R E198137 (UL)
C(UL) CMR UNSH 4/C 14 AWG AUDIO ONLY --- ZONE/DEVICE A B C D E 0
1 2 3 4 5 6 7 8 9 RoHS

Cabled OD Avg: 0.134
Ins Thickness: 0.010
Jkt Thickness: 0.015
Certified: UL CMR/CL3R
Flame Rating: Riser
Max Voltage: 300V

(All of the above values are approximated to within +/- 10%)

3071404.10S.1000