Product data sheet

Specifications

APC NetShelter Basic Rack PDU, 1U, 30A, 208V, 10 C13 outlets



AP9571A

Main

Product or Component Type	PDU
Main Input Voltage	200 V 208 V 230 V
Input current limits	30 A
Input Frequency	50/60 Hz
Main Output Voltage	208 V
Input Connection Type	NEMA L6-30P
Number of power socket outlets	10 IEC 60320 C13
Load Capacity	4992 VA
Line Rated Current	24 A
permissible voltage	200…240 V
Max current draw	24 A
Max line current	30 A
PDU Type	Basic
Protection Type	Circuit breaker
Number of rack unit	1U
Number of cables	1
Cable length	11.98 ft (3.65 m)
Provided Equipment	Installation guide Rack Mounting brackets

Complementary

Mounting Location	Front Rear
Mounting Mode	Rack-mounted
Mounting position	Horizontal
Height	1.7 in (44 mm)
Width	17.5 in (445 mm)
Depth	3.03 in (77 mm)
Net Weight	5.62 lb(US) (2.55 kg)

Environmental

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product Certifications	cUL Listed PSE UL Listed
Standards	UL 60950
Relative Humidity	5…95 %
Storage Relative Humidity	5…95 %
Ambient Air Temperature for Storage	-13…149 °F (-25…65 °C)
Storage altitude	0…50000 ft (0…15240 m)
Operating altitude	0...15000 ft
Ambient Air Temperature for Operation	23…113 °F (-5…45 °C)

Ordering and shipping details

GTIN	731304272755

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	6.7 in (17.1 cm)
Package 1 Width	6.9 in (17.4 cm)
Package 1 Length	19.02 in (48.3 cm)
Package weight(Lbs)	8.02 lb(US) (3.64 kg)

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**8 398 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**0.3 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.3 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**8 385 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.2 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Average percentage of recycled plastic content	**15 %**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
Halogen content performance	**Product contains halogen above thresholds**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**45**
Circularity Profile	**End of Life Information**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Image of product / Alternate images

Alternative

