

CDA6 6" Downlight

Specification Grade Standard Downlight

Product Description

The CDA6 is a 6" downlight in NICOR's Paragon series of specification grade downlights. The CDA6 offers a wide variety of reflector and flange options to fit any architectural or commercial installation. Narrow, medium, and wide optics are easily field installed to customize any space. The CDA6 line features Tri dimming on every fixture, allowing the luminaires to interface with TRIAC, ELV, and 0-10V dimmers down to 1% dimming (with select dimmers). The CDA6 standard light engines come in 16W to 50W packages, with color temperatures ranging from 2700K to 5000K at 80 or 90CRI. The dim-to-warm option provides 3000K full illumination, dimming down to a very warm 1800K at 90CRI. The downlights are available with plaster frame, architectural frame, or remodel housings with J-boxes pre-installed.

Reflector

The CDA6 reflectors are spun from high-grade aluminum. The deep reflectors provide 55° cutoff for excellent glare control. Self-flanged and flangeless options are available in white, specular clear, haze, wheat, black and champagne finishes. Flanges are available in the reflector color or can be painted white. Custom finishes and flange colors are available upon request.*

Optics

The CDA6 family features three standard optics: narrow, medium, and wide distributions. Optics are designed with diffused lenses for smooth, glare-free illumination. Each optic is simple to field install and change with NICOR's twist-lock system. An optional glare shield is available as an accessory for increased glare reduction.

Light Engine

The CDA6 light engine consists of the high-efficiency driver and the LED light module. The module is built from die-cast and extruded aluminum to effectively and efficiently cool the LED and provide longer fixture life. All light engines on the CDA6 are rated for 50,000 hours lifetime at L70. The CDA6 light engine is available in lumen outputs ranging from 1200 to 6000 lumens. Color temperature options include 2700K, 3000K, 3500K, 4000K, and 5000K at 80 or 90CRI. The dim-to-warm option dims from 3000K to 1800K at 90CRI. Color variation on the LED is selected within a 3-step MacAdam ellipse for consistency across fixtures. The CDA6 light module features a quick-connect FMC whip for simple connection to the driver, allowing the light module to be stored in a safe environment while the luminaire housing and driver are installed at rough-in.

Electrical

Drivers in the series operate on 120-277VAC. The high-efficiency drivers feature Tri dimming, seamlessly interfacing with TRIAC & ELV dimmers on 120VAC input, and 0-10V systems on 120-277VAC (down to 1% with select dimmers). The CDA6 driver comes with two flexible metal conduit (FMC) whips installed: one end featuring line voltage and 0-10V dimmer wiring with a conduit connector for simple J-box installation, the other with a quick-connect for easy connection to the light module. CDA6 Class 2 drivers are available in 16W, 25W, 38W and 50W packages with a power factor of >.90.

Controls

CDA fixtures are available with NICOR NLC (Network Lighting Controls) which feature a Bluetooth Low Energy (BLE) mesh network providing Luminaire Level Lighting Control (LLLC). Mounted to the frame, the integrated power supply relay (optional) allows for field installed BLE PIR/Daylight sensor (ND) which is shipped with luminaire. The control system provides full dimming control with occupancy and daylight harvesting functions and features are configurable with the NICOR NLC app available on iOS and Android devices.

See www.nicorlighting/network-lighting-controls for more information and NLC Data Sheets

Housings

CDA6 housings are made of 16ga. powder-coated and galvanized steel construction, making them attractive, rugged, and corrosion resistant. The architectural housing provides butterfly brackets adjustable for up to 2" ceiling thickness, while the plaster frame comes with adjustable, stamped bar hangers to fit a range of joist spacings between 14 3/8" and 25 1/8". The remodel frame is supplied with four arch clips for simple, robust through-ceiling remodel installation. All frames have wing springs to mount the reflector, a safety-wire hook for light engine retention, and junction box with six 1/2" knockouts, one 3/8" knockout, and four non-metallic sheathed cable knockouts. Junction boxes are rated for eight 12AWG 90°C rated wires.

Installation

The CDA6's modular design is focused on ease of installation, allowing installers to rough-in the housing and driver while safely storing the trim and light engine until after ceiling work is complete. The reflector twists onto the light engine with three keyholes and screws. The twist-lock optic installs tool-free for quick installation and change-out. Once the reflector and optic are installed, simply slide the light engine into the frame where it is retained by wing springs.

Warranty

The NICOR Paragon family comes with our 5-year limited system warranty standard.

Code Compliance

UL Listed for wet locations in covered ceilings only. Non-IC rated, insulation must be kept 3" away from the top and sides of the housing. Photometric testing completed in accordance with IES LM-79

Project

Catalog

Type

Date



CDA6
16W, 25W, 38W, 50W
6" Downlight
Architectural
Remodel
Plaster Frame



* Contact factory for lead time and minimum order quantity.

CDA6 6" Downlight


Specification Grade Standard Downlight

Photometric Data

CDA6 Narrow Optic

3500K 38W 90CRI

Input Voltage (VAC)	120/277
System Level Power (W)	38.6
Delivered Lumens (Lm)	3718
System Efficacy (Lm/W)	96.3
Correlated Color Temp (K)	3487
Color Rendering Index (CRI)	92
Beam Angle	26.5
Spacing Criteria	0.43



Adjustment Multipliers

Trim Color	CCT	Wattage	CRI
WH=104%	27K=92%	16=38%	80=117%
SC=105%	30K=98%	25=57%	90=100%
CZ=100%	35K=100%	38=100%	
GL=99%	40K=104%		
BK=78%	50K=108%		
CM=99%			

Cone of Light Tabulation

Mounted height (Feet)	Footcandles Beam Center	Diameter (Feet)
4	647.1	2.4
6	287.6	2.8
8	161.8	4.0
10	103.5	5.0
12	71.9	5.2
14	52.8	6.0
16	40.4	7.0

Intensity Summary (Candle Power)

Angle	Mean CP
0	1035
5	9282
15	4337
25	2142
35	736
45	157
55	58
65	18
75	9
85	1
90	0

Zonal Lumen Summary

Zone	Lumens	% of Luminaire
0-30	3008	81%
0-40	3508	94%
0-60	3688	99%
0-90	3718	100%

EM Mode*

EMB	Estimated Lumens
EMB45	432
EMB80	768
EMB250	2400


*Estimated lumen output is based on lumens per watt of the 3500K 38W test fixture and the wattage of the EM driver. For a better estimate of a specific part number, determine the fixture efficiency and use the formula:
EM Lumens = Lm/W Fixture x EM driver Wattage

Fixture tested per LM-79-08. Photometric data is of the performance of a representative fixture. Results may vary in the field.

CDA6 Medium Optic

3500K 38W 90CRI

Input Voltage (VAC)	120/277
System Level Power (W)	38.6
Delivered Lumens (Lm)	3674
System Efficacy (Lm/W)	95.2
Correlated Color Temp (K)	3494
Color Rendering Index (CRI)	91
Beam Angle	43.9
Spacing Criteria	0.66



Adjustment Multipliers

Trim Color	CCT	Wattage	CRI
WH=104%	27K=92%	16=38%	80=117%
SC=105%	30K=98%	25=57%	90=100%
CZ=100%	35K=100%	38=100%	
GL=99%	40K=104%		
BK=78%	50K=108%		
CM=99%			

Cone of Light Tabulation

Mounted height (Feet)	Footcandles Beam Center	Diameter (Feet)
4	384.0	2.8
6	170.6	4.0
8	96.0	5.2
10	61.4	6.4
12	42.7	8.0
14	31.3	9.4
16	24.0	10.8

Intensity Summary (Candle Power)

Angle	Mean CP
0	6143
5	5801
15	4244
25	2603
35	824
45	174
55	58
65	19
75	9
85	1
90	0

Zonal Lumen Summary

Zone	Lumens	% of Luminaire
0-30	2891	79%
0-40	3448	94%
0-60	3643	99%
0-90	3674	100%

EM Mode*

EMB	Estimated Lumens
EMB45	427
EMB80	760
EMB250	2375

*Estimated lumen output is based on lumens per watt of the 3500K 38W test fixture and the wattage of the EM driver. For a better estimate of a specific part number, determine the fixture efficiency and use the formula:
EM Lumens = Lm/W Fixture x EM driver Wattage

Fixture tested per LM-79-08. Photometric data is of the performance of a representative fixture. Results may vary in the field.

CDA6 6" Downlight


Specification Grade Standard Downlight

Photometric Data

CDA6 Wide Optic

3500K 38W 90CRI

Input Voltage (VAC)	120/277
System Level Power (W)	38.7
Delivered Lumens (Lm)	3681
System Efficacy (Lm/W)	95.1
Correlated Color Temp (K)	3513
Color Rendering Index (CRI)	92
Beam Angle	57.1
Spacing Criteria	0.80



Adjustment Multipliers

Trim Color	CCT	Wattage	CRI
WH=104%	27K=92%	16=38%	80=117%
SC=105%	30K=98%	25=57%	90=100%
CZ=100%	35K=100%	38=100%	
GL=99%	40K=104%		
BK=78%	50K=108%		
CM=99%			

Cone of Light Tabulation

Mounted height (Feet)	Footcandles Beam Center	Diameter (Feet)
4	293.0	3.2
6	130.2	4.8
8	73.3	6.0
10	46.9	7.4
12	32.6	9.2
14	23.9	10.8
16	18.3	12.2

Intensity Summary (Candle Power)

Angle	Mean CP
0	4688
5	4394
15	3436
25	2717
35	1147
45	265
55	74
65	24
75	12
85	2
90	0

Zonal Lumen Summary

Zone	Lumens	% of Luminaire
0-30	2593	70%
0-40	3349	91%
0-60	3642	99%
0-90	3681	100%

EM Mode*


EMB	Estimated Lumens
EMB45	427
EMB80	760
EMB250	2375

*Estimated lumen output is based on lumens per watt of the 3500K 38W test fixture and the wattage of the EM driver. For a better estimate of a specific part number, determine the fixture efficiency and use the formula:
EM Lumens = Lm/W Fixture x EM driver Wattage


Fixture tested per LM-79-08. Photometric data is of the performance of a representative fixture. Results may vary in the field.

Housings


Plaster Frame



Architectural Frame




Remodel Frame



CDA6 6" Downlight


Specification Grade Standard Downlight

Light Engine & Trim




Trim Styles


Self-Flanged




Flangeless



Flangeless Adapter



Glare Shield



CDA6 6" Downlight

Specification Grade Standard Downlight

Ordering Information

Housing

Example: CDA6H2R

Series	Version	Style	Controls	Emergency
CDA6HS	2	A (Architectural)	Blank (None)	E1 (EMB45)
		F (Plaster Frame)	ND (NLC Controls)	E2 (EMB80)
		R (Remodel)		E3 (EMB250)

Light Engine

Example: CDALE2016U278

Series	Version	Wattage	Voltage	CCT	CRI
CDALE	2	016 (16 Watts)	U (120-277VAC)	27 (2700 K)	8 (80 CRI)
		025 (25 Watts)		30 (3000 K)	9 (90 CRI)
		038 (38 Watts)		35 (3500 K)	
		050 (50 Watts)		40 (4000 K)	
				50 (5000 K)	
				DW (Dim to Warm) ¹	

¹Dim to Warm only available at 90CRI on 16W, 25W, and 38W fixtures

Trim and Optic

Example: CDA6TR220WHSF

Series	Version	Optic	Reflector	Flange
CDA6TR	2	20 (Narrow Optic)	WH (White)	SF (Self-flanged)
		40 (Medium Optic)	SC (Specular Clear)	WH (White)
		60 (Wide Optic)	CZ (Clear Haze)	FL (Flangeless)
			GL (Wheat)	CUST (Custom)
			BK (Black)	
			CM (Champagne)	
			CUST (Custom)	

Accessories

Reflector

Series	Version	Reflector	Flange
CDA6RFL	2	WH (White)	SF (Self-flanged)
		SC (Specular Clear)	WH (White)
		CZ (Clear Haze)	FL (Flangeless)
		GL (Wheat)	CUST (Custom)
		BK (Black)	
		CM (Champagne)	
		CUST (Custom)	

Flangeless Adapter

Series

CDA6FLNGLESADAPT

Optics

Series	Version	Style
CDAOP	2	20 (Narrow Optic)
		40 (Medium Optic)
		60 (Wide Optic)

Glare Shield

Series	Version	Style
CDA6GS	2	WH (White)
		SC (Specular Clear)
		CZ (Clear Haze)