



PDU15M2F10R METERED PDU



Engineered to distribute UPS, generator or utility AC power to multiple devices, servers and network/telecom equipment.

The CyberPower PDU15M2F10R, a 12-outlet (two front, ten rear), rackmount metered power distribution unit (PDU), provides 100 - 125 V 15A output. It distributes power to 12 NEMA 5-15R receptacles from a single NEMA 5-15P input with unfiltered electrical pass-through. The current draw for connected equipment is displayed in amps on the front LCD for real-time load monitoring.

Designed for datacenters and other electrically demanding applications, the PDU15M2F10R has rugged, industrial-grade metal housing and a 15-foot AC power cord. It can be mounted either horizontally or vertically. The PDU15M2F10R comes with a cord retention tray and is ETL/RoHS certified. A limited lifetime warranty covers defects in materials and workmanship in the product under normal use and conditions.

TYPICAL APPLICATIONS

- Corporate Servers
- Network Closets
- Data Centers

FEATURES

- Digital meter: Displays Amperage
- Phase: Single
- Amps: 15A (Derated to 12A)
- Volts: 100 - 125 V
- Frequency: 50Hz/60Hz
- Plug type: NEMA 5-15P
- Outlets: 12 x NEMA 5-15R
- Outlet location: 2 Front / 10 Rear
- Size: 1U Rackmount
- Dimensions (in.): 17.5W x 1.75H x 2.25D
- Cord length (ft.): 15
- Warranty: Limited Lifetime

SPECIFICATIONS

INPUT	
Cord Length (ft.)	15 ft (4.6 m)
Derated Input Current	12 A
Input Frequency Range	50Hz - 60Hz
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Straight

OUTPUT	
Meter Readout	Amperage
Nominal Output Voltage	100 - 125 VAC
Outlet Type	12 x NEMA 5-15R
Outlets - Front	2
Outlets - Rear	10
Outlets - Total	12
Overload Protection	15 A

PDU15M2F10R METERED PDU



SPECIFICATIONS

PHYSICAL		SHIPPING DIMENSIONS	
Adjustable Mounting Brackets	2 sets (L-Short, L-Long)	Shipping Dimensions - Width/Height/Depth (cm)	15.39 x 6.99 x 51.44 cm
Color	Black	Shipping Dimensions - Width/Height/Depth (mm)	153.92 x 69.85 x 514.35 mm
Cord Retention Tray/ Cord Organizers	Yes	Shipping Dimensions - Width/Height/Depth (in.)	6.06 x 2.75 x 20.25 in.
External Site Ground Pin	Yes	Shipping Weight (kg)	2.49 kg
Form Factors Supported	1U Rackmount Undercounter Installation Supported	Shipping Weight (lbs.)	5.5 lbs.
Material of Construction	Metal	ENVIRONMENTAL	
Rack Height	1U	Operating Elevation	0 - 10,000 ft (0 - 3,048 m)
Style	Rackmount Vertical Rackmount Under-Counter	Operating Relative Humidity	0 - 95% (non-condensing)
		Operating Temperature	32 - 95 °F (0 - 35 °C)
PHYSICAL DIMENSIONS		Storage Elevation	0 - 50,000 ft (0 - 15,239 m)
Physical Dimensions - Width/Height/Depth (cm)	44.45 x 4.45 x 5.72 cm	Storage Temperature	5 - 113 °F (-15 - 45 °C)
Physical Dimensions - Width/Height/Depth (mm)	445 x 44 x 57 mm	CERTIFICATIONS	
Physical Dimensions - Width/Height/Depth (in.)	17.5 x 1.75 x 2.25 in.	Environmental	RoHS Compliant
Weight (kg)	1.81 kg	Safety	UL62368 UL60950-1 FCC Class A
Weight (lbs.)	4.0 lbs.	WARRANTY	
		Product Warranty	Limited Lifetime Warranty