


Parkette

WARM COLORS OF PARKETTE EVOKE IMAGES
OF KILN-FIRED BRICKS.



Parkette Gray 4x8

Colors



Stone VTL PAST



Gray VTL PAGR



Burnt VTL PABU



Red VTL PARD



Silver Flash VTL PASV



Ash Flash VTL PAAS



Sienna Flash VTL PASI



Mahogany Flash
VTL PAMA

Sizes



6" x 6" x 12.7mm

Abrasive


- Stone
- Gray
- Burnt
- Red
- Ash Flash
- Sienna Flash



6" x 6" x 12.7mm

Matte


- Stone
- Gray
- Burnt
- Red
- Silver Flash
- Ash Flash
- Sienna Flash
- Mahogany Flash



8" x 8" x 12.7mm

Abrasive

- Gray
- Red



8" x 8" x 12.7mm

Matte

- Gray
- Red
- Silver Flash
- Mahogany Flash

PARKETTE

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
6" x 6"	6" x 6"	12.7 mm	Abrasive & Matte
8" x 8"	8" x 8"	12.7 mm	Abrasive & Matte


*Not all sizes/trims are available in all colors and finishes

Mosaics & Coordinating Trims*

SIZE	FINISH
8" x 8" Bullnose	Matte
6" x 6" Bullnose	Abrasive & Matte
5" x 8" Cove Base	Matte
5" x 6" Round Top Cove Base	Matte
5" x 6" Round Top Cove Base Corner Left	Matte
5" x 6" Round Top Cove Base Corner Right	Matte
1" x 5" Cove Base Inside Corner	Matte

Product Characteristics

TEST	ABRASIVE	MATTE
Breaking Strength	>350 lbs	>400 lbs
Chemical Resistance	Resistant	Resistant
DCOF	≥0.65	≥0.60
Deep Scratch Resistance - Unglazed	Not Applicable	Not Applicable
Frost Resistance	Not Applicable	Not Applicable
Mohs Hardness - EN101	7	7
Water Absorption	<3.0	<3.0
Certifications	Not Applicable	Not Applicable
Country of Origin	USA	USA
Shade Variation Code	v3, v4	v3, v4



V3 Moderate Variation



DCOF ≥0.65 - Abrasive
DCOF ≥0.60 - Matte



V4 Substantial Variation



Water Absorption: <3.0%



Made in USA

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	•
Exterior	Residential/Commercial	•	•

** These recommendations are not defined by ANSI Standards

Material

Quarry



Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com



VITL
COMMERCIAL SURFACES