



TECHNICAL INFORMATION



V3 Moderate
Variation



Ready Ship
Stock



Recommend offset
pattern $\leq 33\%$



DCOF: ≥ 0.42



Frost Resistant



Water Absorption:
 $< 0.5\%$




COLORS



Brown
VTC BDBR



Ivory
VTC BDIV



Gray
VTC BDGR

Performance Characteristics

Breaking Strength	≥ 425 lbs
Chemical Resistance	Resistant
DCOF	≥ 0.42
Deep Scratch Resistance - Unglazed	N/A
Frost Resistance	Resistant
Mohs Hardness - EN101	N/A
Water Absorption	$< 0.5\%$
Certifications	N/A
Country of Origin	N/A
Shade Variation Code	V3

Tiles, Mosaic and Trim*

SIZE	ACTUAL	THICKNESS	FINISH
12" x 24" Rectified	11.75" x 23 9/16"	9 mm	Honed
24" x 24" Rectified	23 9/16" x 23 9/16"	9 mm	Honed
24" x 48" Rectified	23 9/16" x 47 5/16"	9 mm	Honed
2" x 2" Mosaic Rectified	11.75" x 11.75"	9 mm	Honed
4" Chevron Mosaic Rectified	11 9/16" x 14 4/16"	9 mm	Honed
3" x 12" Bullnose Rectified	2.75" x 11.75"	9 mm	Honed

* Not all sizes are available in all colors and finishes.

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	

** These recommendations are not defined by ANSI Standards



Please see virginiatile.com for details