



SKU: PCT-8-4/0

UPC: 0783669700541

Features & Benefits:

Description: Cleartap Insulated Aluminum Multi-Tap Connector, Dual Rated, Conductor Range 4/0-6, 8 Ports, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	8
Number of Poles	1
Number of Ports / Wireways	8
Number of Usable Ports	8

Dimensions

Drive Size Main	5/16
Drive Type Main	Internal Hex
Height (IN)	2.251
Height BX (IN)	6
Height (mm)	57.1754
Length (IN)	8.033
Length (mm)	204.0382
Max Insulation OD (IN)	0.74
Max Insulation OD (mm)	18.796
Weight (LB)	0.781
Weight BX (LB)	5.0879
Width (IN)	2.461
Width BX (IN)	10.75
Width (mm)	62.5094

Material and Finish

Connector Finish	Tin
Insulation	Plastisol
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	9/16
Wire Binding Torque	275

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366970054

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	4/0 Str - 6 Str
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	4/0 Str - 6 Str
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 14 Sol
Flex Conductor Range	NA

Color

Color	Clear
-------	-------

Additional Technical Specifications

Connector Amperage Rating CU (Derated where applicable)	260 Amps
Conductor Type	Solid

Voltage

Voltage Rating	600 V
----------------	-------

Environment and Temperature

Environmental Conditions	Cold temperature rated to -45°C
Flammability Rating	Insulation rated per UL 94
Temperature Rating	90°C